



**City of Dearborn**

**INVITATION TO BID (ITB) FOR  
POOL CONSTRUCTION AT THE FORD  
WOODS PARK**

**CONTROL No. 122972  
ADDENDUM No. 2**

**ISSUE DATE: 11/16/17**

**DUE DATE: 12/06/17 AT 3:00 p.m. Local Time**

This addendum is being issued to modify some sections of the ITB, as well as to distribute additional plans/specifications and the sign-in sheet from the pre-bid meeting held on 11/13/17.

Refer to the attached sections and drawings:

- Addendum 2 document provided by TMP Architecture – 3 pages
- Section 012300 – Section Alternates – 2 pages
- Section 082250 – FRP Doors and Aluminum Frames for FRP Doors – 7 pages
- Section 105129 – Phenolic Lockers – 4 pages
- Section 221413 – Storm Drainage Piping – 7 pages
- Section 221429 – Sump Pumps – 5 pages
- Drawings – C1.3, S1.0, M2.0, M2.1, M6.2, M7.1, M7.2, E0.3, E2.1, E3.1, E5.1
- Sign-in sheet from the pre-bid meeting held on 11/13/17.

Reminders:

Pre-bid question deadline – November 29, 2017 at 12:00 p.m. local time. All questions are to be submitted in writing to the Buyer listed on the cover page of the solicitation.

Bid deadline – December 6, 2017 at 3:00 p.m. local time. All bids are to be uploaded to the MITN website.

All other terms and conditions remain unchanged.

Carrie Darkowski  
Buyer  
[cdarkowski@ci.dearborn.mi.us](mailto:cdarkowski@ci.dearborn.mi.us)

**THIS ADDENDUM MUST BE ACKNOWLEDGED ON THE RESPONSE FORM IN THE ITB**



## ADDENDUM

DATE: November 16, 2017

PROJECT: City of Dearborn - Ford Woods Park Pool

TMP PROJECT NO.: 17071

ADDENDUM NO.: Two

**ADDENDUM NO. 1 WAS PREVIOUSLY ISSUED ON NOVEMBER 9, 2017.**

The Bidding Documents are modified, supplemented or augmented as follows and this Addendum is hereby made a part of the proposed Contract Documents.

The following Drawings and attachments are issued with this Addendum.

Drawing No.: C1.3, S1.0, M2.0, M2.1, M6.2, M7.1, M7.2, E0.3, E2.1, E3.1, E5.1

Attachments: Specification Sections 012300, 082250, 105129, 221413, 221429

### ITEM NO.      SPECIFICATION CHANGES

SC-1      Refer to TABLE OF CONTENTS (not reissued):

- A. Added specification sections "012300 Alternates," "221413 Storm Drainage" and "221429 Sump Pumps" to the Table of Contents.

SC-2      Refer to Section 012300 – ALTERNATES (new):

- A. Added specification section to project.

SC-3      Refer to Section 082250 – FRP DOORS AND ALUMINUM FRAMES FOR FRP DOORS (reissued):

- A. Added paragraph 2.1.A.2 as indicated.

SC-4      Refer to Section 105129 – PHENOLIC LOCKERS (reissued):

- A. Added paragraph 2.1.A.4 as indicated.

SC-5      Refer to Section 131100 – SWIMMING POOL (not reissued):

- A. Deleted paragraphs 1.3.A.2 and 1.3.A.3.
- B. Revised paragraph 2.2.A.5 to add the following sentence:

"All strainers shall be equipped with a bleed valve."

o:\2017\17071\specs\addenda\addendum 2\17071 add02.docx

SC-6 Refer to Section 221413 – STORM DRAINAGE PIPING (new):

- A. Added specification section to project.

SC-7 Refer to Section 221429 – SUMP PUMPS (new):

- A. Added specification section to project.

ITEM NO.      CIVIL DRAWING CHANGES

CD-1 Refer to Drawing No. C1.3 (reissued):

- A. Revised location and design of 8" sanitary lead on the north side of the proposed building as indicated.
- B. Revised location and design of 6" sanitary lead on the northwest corner of the proposed building as indicated.
- C. Added 6" storm lead to connect to INL A1.3 as indicated.
- D. Revised storm system design from INL A1.3 to FCB A1 as indicated.
- E. Revised utility crossings 6 and 7 as indicated.

ITEM NO.      STRUCTURAL DRAWING CHANGES

SD-1 Refer to Drawing No. S1.0 (reissued):

- A. Modified bottom of footings at north side of proposed building as indicated.

ITEM NO.      MECHANICAL DRAWING CHANGES

MD-1 Refer to Drawing No. M2.0 (reissued):

- A. Relocated 8" sanitary serving surge tank as indicated.
- B. Revised the location of the 4" sanitary on the west side of the building as indicated.
- C. Added drain tile and connections around surge tank as indicated.
- D. Added drain tile and connections around pump pit as indicated.
- E. Added sump pump basin as indicated.
- F. Removed floor drains in pump pit as indicated.
- G. Modified sanitary routing as indicated.
- H. Revised the sanitary size from 3" to 4" serving floor drain (FD-3) as indicated.
- I. Revised floor drain from FD-1 to FD-3 as indicated in Storage 106.
- J. Revised floor drain from FD-1 to FD-2 as indicated in Storage 106.
- K. Added storm piping to five feet outside the building as indicated.

MD-2 Refer to Drawing No. M2.1 (reissued):

- A. Removed two floor drains (FD-2) from the pump it as indicated.
- B. Added Sump Pump (SP-1) and discharge piping as indicated.
- C. Added Control Panel for SP-1 as indicated.
- D. Added discharge piping routed south through Mechanical Room, Storage Room, and Janitors closet as indicated.
- E. Added notes associated with sump pump discharge piping as indicated.

- F. Added Construction Note #7 as indicated.
- G. Added Construction Note #8 as indicated.

MD-3 Refer to Drawing No. M6.2 (reissued):

- A. Added Sump Pump Detail as indicated.

MD-4 Refer to Drawing No. M7.1 (reissued):

- A. Added Underground Storm Drainage to Plumbing Piping and Valve Schedule as indicated.
- B. Added Aboveground Pumped Storm for corrosive and non-corrosive environments to the Piping to Plumbing Piping and Valve Schedule as indicated.

MD-5 Refer to Drawing No. M7.2 (reissued):

- A. Added Sump Pump Schedule as indicated.
- B. Modified Pump Schedule as indicated.

ITEM NO.            ELECTRICAL DRAWING CHANGES

ED-1 Refer to Drawing No.E0.3 (reissued):

- A. Added branch circuiting and controls for underwater lighting as indicated.
- B. Added remote push button station for water slide pumps at top of water slide as indicated.

ED-2 Refer to Drawing No.E2.1 (reissued):

- A. Added branch circuiting and controls for underwater lighting.

ED-3 Refer to Drawing No.E3.1 (reissued):

- A. Added branch circuiting for sump pump SP-1.

ED-4 Refer to Drawing No. E5.1 (reissued):

- A. Added GFI breakers for pump room equipment as indicated.
- B. Added breaker for sump pump SP-1

\*\*END OF ADDENDUM NO. 2\*\*

ALTERNATES

PART 1 – GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of Contract, including General and Supplementary Conditions and Division 1 Specification sections, apply to work of this section.

1.2 DESCRIPTION OF REQUIREMENTS:

- A. Definition: An alternate is an amount proposed by Bidders and stated on the Bid Form that will be added to or deducted from Base Bid amount if the Owner decides to accept a corresponding change in either scope of work or in products, materials, equipment, systems or installation methods described in Contract Documents.
- B. Coordination: Coordinate related work and modify or adjust adjacent work as required to ensure that work affected by each accepted alternate is complete and fully integrated into the project.
- C. Notification: Immediately following award of Contract, prepare and distribute to each party involved, notification of the status of each alternate. Indicate whether alternates have been accepted, rejected or deferred for consideration at a later date. Include a complete description of negotiated modifications to alternates, if any.
- D. Schedule: A "Schedule of Alternates" is included at the end of this section. Specification sections referenced in the Schedule contain requirements for materials and methods necessary to achieve the work described under each alternate.
  - 1. Include as part of each alternate, miscellaneous devices, appurtenances and similar items incidental to or required for a complete installation whether or not mentioned as part of the alternate.

PART 2 - PRODUCTS (not applicable)

PART 3 - EXECUTION

3.1 SCHEDULE OF ALTERNATES

- A. Alternate No. 1: Pool Slide

Base Bid: Fiberglass waterslides and tower structure detailed on drawings and specified in section 131413.

Alternate Bid: 76' Poolslide Waterslide, item #65-370. See specification section 131100 "SWIMMING POOL", paragraph 1.6 for further information.

- B. Alternate No. 2: Phenolic Lockers

Base Bid: Phenolic lockers in size, configuration, and layout detailed on drawings and specified in section 105129.

Alternate Bid: In lieu of Base Bid, provide pricing for stainless steel lockers in same footprint and similar height and tier configuration. Stainless steel lockers to be 304 grade with sloped

tops. Provide pricing based upon stainless steel lockers provided by one of the following manufacturers:

1. Art Metal Products – 304 Stainless Steel KD Wardrobe Lockers
2. List Industries Inc. – 304 Stainless Steel Lockers
3. Olympus Lockers – Poseidon Stainless Steel Lockers

**\*\*END OF SECTION\*\***

FRP DOORS AND ALUMINUM FRAMES FOR FRP DOORS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS/DESCRIPTION

- A. Drawings and General provision of Contract, including General and Supplementary Conditions and Division 01 Specification sections, are a part of this Section for the Base Bid and applicable alternates.
- B. This Section includes:
  - 1. FRP doors - provide FRP doors as specified, shown or scheduled, with components and accessories for a complete and proper installation.
  - 2. Factory glazing of FRP door lites.
  - 3. Factory installation of finish hardware.
  - 4. Aluminum frames for FRP doors.
- C. The following sections contain requirements that relate to this Section:
  - 1. Division 7 Section "Joint Sealants" for sealants and gaskets.
  - 2. Division 8 Section "Glazing" for glass and glazing.
  - 3. Division 8 Section "Door Hardware" for door hardware.
- D. System Performance:
  - 1. Provide exterior and interior doors assemblies that have been designed and fabricated to comply with requirements for system performance characteristics listed below as demonstrated by testing manufacturer's corresponding stock systems according to test methods designated.
    - a. Thermal Transmittance (exterior doors): U-value of not more than 0.09 Btu/(hr x sf x Degrees F.) per AAMA 1503.1.

1.2 QUALITY ASSURANCE

- A. Comply with fire-resistance, flammability, regulations as interpreted by governing authorities and as follows:
  - 1. Face Sheets tested in accordance with ASTM E84-79A shall have the following ratings; Standard Face sheets:
    - a. Smoke Developed: not greater than 345.
    - b. Flame Spread: not greater than 145.
  - 2. Class A Face Sheets (Required on interior face of all exterior doors):

- a. Smoke Developed not greater than 340.
  - b. Flame Spread: not greater than 15.
- B. Manufacturer Qualifications: Shall have produced fiberglass reinforced doors for at least five years.
- C. Field Measurement:
- 1. Take field measurements prior to fabrication of doors and frames to insure proper fitting of assemblies. Successful bidders are expected to field verify all dimensions, sizes, quantities and the material required to complete this project. Failure to do so will not relieve the successful contractor from the necessity of furnishing any and all materials that may be required, without any additional cost to the Owner.

### 1.3 COORDINATION

- A. Door manufacturer shall be responsible for coordinating all necessary information from hardware supplier in order that doors shall be properly prepared to receive hardware and fit frames properly. Contractor shall provide manufacturer with copies of approved schedules necessary to complete manufacturing of doors. This information shall be in the possession of the door manufacturer 60 days prior to desired delivery date of doors.

### 1.4 SUBMITTALS

- A. General: Submit the following in accordance with Conditions of Contract and Division 1 Specification Sections.
- 1. Substitutions for products as specified MUST be submitted in accordance with Division 1. Substitute products not submitted in accordance with Division 1 Section "Product Requirements" will NOT be considered.
- B. Product Data: Submit manufacturer's specifications, standard details, and installation recommendations for components of FRP (fiberglass reinforced polyester) doors required for project, including test reports certifying that products have been tested and comply with performance requirements.
- C. Shop Drawings: Submit shop drawings for fabrication and installation of FRP (fiberglass reinforced polyester) doors, including elevations, detail sections of typical composite members, hardware mounting heights, anchorages, reinforcement, expansion provisions, and glazing.
- D. Samples: Submit 6" samples of each type and color of FRP (fiber reinforced polyester) finish, and 12" long sections of extrusions or formed shapes. Where normal color and texture variations are to be expected, include 2 or more units in each set of samples showing limits of such variations.

### 1.5 PRODUCT DELIVERY, HANDLING, AND STORAGE

- A. All materials supplied shall be delivered to the jobsite in their original, unopened packages with labels intact. Materials shall be inspected for damage, and the manufacturer informed of any discrepancies. Unsatisfactory materials shall not be used.
- B. All materials supplied shall be packaged in individual corrugated cartons. Doors shall "floated" within cartons, with no portion of door in contact with outer shell.

- C. All doors to be marked with individual opening numbers to correlate with the designation system used on the shop drawings for doors, frames and hardware. Markings shall be temporary, removable, or concealed.

#### 1.6 WARRANTY

- A. Provide written warranty signed by Manufacturer, Installer, and Contractor, agreeing to replace FRP (fiberglass reinforced polyester) doors which fail in materials or workmanship within time period indicated below of acceptance. Failure of materials or workmanship includes excessive deflections, faulty operation of entrances, and deterioration of finish or construction in excess of normal weathering.

- 1. Time Period: 10 years from date of shipment. In addition, a limited lifetime (while the door is in its specified application in its original installation) warranty covering: failure of corner joinery, core deterioration, delamination or bubbling of door skin.

- B. Provide written warranty signed by Manufacturer guaranteeing hardware attachment of factory installed finish hardware.

- 1. Time Period: 10 years from date of shipment.

#### PART 2 - PRODUCTS

##### 2.1 ACCEPTABLE MANUFACTURERS

- A. **Basis of Design Product:** Subject to compliance with requirements, provide SL17 FRP Flush Doors as manufactured by Special-Lite, Inc., and Aluminum Frames for FRP Doors as specified herein. **Provide either the named product or a comparable product by one of the following:**

- 1. **CORRIM Company \*\*ADD01\*\***

- 2. **Vale Doors \*\*ADD02\*\***

##### 2.2 MATERIALS AND ACCESSORIES

- A. Aluminum Members: Alloy and temper recommended by manufacturer for strength, corrosion resistance, and application of required finish; ASTM B 221 for extrusions, ASTM B 209 for sheet/plate, minimum wall thickness of 1/8".

- B. Fasteners: Aluminum, or other materials warranted by manufacturer to be non-corrosive and compatible with aluminum components.

- 1. For exposed fasteners, provide Phillips head flat head screws with finish matching item to be fastened.

- C. Brackets and Reinforcements: Manufacturer's high-strength aluminum units where feasible; otherwise provide nonmagnetic stainless steel or hot-dip galvanized steel complying with ASTM A 386.

- 1. Provide manufacturer's standard reinforcement for each type of hardware required, not less than .125" thick.

- 2. Provide manufacturer's recommended fastener reinforcement.

- D. Door Face Material: Fiberglass reinforced polyester, SpecLite 3, 0.120" minimum thickness, with pebble-like embossed finish.
1. Acceptable Product: Subject to compliance with the following requirements:
    - a. Impact Strength of Face Sheets: ASTM D256, Izod Impact Strength, 13.5 footpounds per inch of notch.
    - b. Abrasion Resistance of Face Sheets: ASTM D1242, 1000 cycles of Model 503 Taber Abraser with a 1000 gram load, not to exceed 0.23% weight loss.
    - c. Hardness of Face Sheets: ASTM D2583, Barcol Meter Hardness Test, not more than 50.
    - d. Humidity Resistance of Face Sheets: ASTM D570, water absorption not greater than 0.40% after 24 hour immersion.
    - e. Ultra-Violet Degradation: Only slight color change, and negligible change in surface gloss and other physical properties after exposure to 500,000 Langleys.
- E. Weatherstripping: Provide manufacturer's standard replaceable weathering pile.
- F. Sweep: Provide manufacturer's adjustable sweep.
- G. Sealants and Gaskets: Provide sealants and gaskets in the fabrication, assembly and installation of the work, which are recommended by the manufacturer to remain permanently elastic, non-shrinking, non-migrating, and weatherproof.

## 2.3 FIBERGLASS REINFORCED POLYESTER (FRP) DOORS

- A. FRP Doors are to be constructed as follows:
1. Doors are to be 1 3/4" thick.
  2. Constructed of aluminum alloy rails and stiles, joined with steel tie rods, and have an inner core consisting of foamed-in-place Urethane.
  3. Stiles to be tubular shape to accept hardware as specified.
  4. Top and bottom rails to be extruded with internal legs for interlocking rigid weather bar.
  5. Face Sheets to be secured with extruded interlocking edges. (No snap-on trim will be accepted).
  6. Joinery to be 3/8" tie rods, top and bottom, bolted through an extruded spline and 3/16" riveted reinforcing angles, and secured with hex nuts.
  7. Core to be of Urethane foam of 5 pounds per cubic ft. density. All doors are to be properly reinforced for hardware prior to Urethane core foaming in door.
  8. Face Sheets:
    - a. Fiberglass Reinforced Plastic Sheets to be polyester SpecLite 3, 0.120" thick, with pebble-like finish.
  9. Pairs of Doors: Meeting stiles to beveled.
  10. All doors shall be machined for finish hardware at the factory in accordance with the templates from the hardware supplier and the Approved Hardware Schedule. For

surface applied hardware, doors shall have necessary reinforcement, including the attachment of RIVNUT blind bolt fasteners. With the exception of door holders, which require field application, doors are to be shipped with surface hardware factory applied.

11. Door Lites: Provide door lites factory glazed as indicated, with manufacturer's standard aluminum moldings and stops, with removable stops on inside only. Glass to be 1" insulated safety glass.

#### 2.4 FLUSH INSULATED PANELS

- A. Flush insulated panels shall be constructed as follows:

1. Panels shall be 1" thick.
2. Panel stiles shall be formed of hardwood.
3. Core to be Urethane of 5 pounds per cubic foot density.
4. Face Skins to be as follows:
  - a. Fiberglass Reinforced polyester panel faces to be SpecLite 3, 0.120" thick, with pebble-like embossed finish.

#### 2.5 ALUMINUM DOOR FRAMING FOR FRP DOORS (Required for all immediate door frames with FRP doors).

- A. Frame Members: Frame members to be one piece tubular extrusions of 6063 T5 aluminum alloy with minimum wall thickness of 1/8".
- B. Reinforcement: Frames shall be internally reinforced and factory prepared for specified finish hardware.
- C. Stops: Provide applied door stops at single acting doors. Stops to be caulked and weathertight by installer in field.
- D. Fabrication: Fabricate tubular frame assemblies as shown. Vertical frame members are to be the full height of the entrance opening. Joints are to be reinforced with internal anchors so that vertical and horizontal frame members are physically interlocked.
- E. Glazing: Provide glazing system for doors and frames to receive lites. Design system for replacement of glass/panel, but for non-removal of glass/panel from the exterior. Ship frame members to jobsite with glazing bead installed and caulked on secure side of frame.

#### 2.6 ALUMINUM CAPPING SYSTEM

- A. Where indicated, provide a Frame capping system fabricated of .062" Aluminum, as manufactured by Special-Lite, Inc. Finish capping to match finish as supplied on other framing sections.

2.7 INSERT FRAMING

- A. Where indicated, provide insert frames fabricated of extruded 6063T5 Aluminum alloy fitted with .34 inch high by .36 inch wide wool-poly-propylene blend pile. Corner joints are to be mitered and secured with prefabricated aluminum clips. Framing as manufactured by Special-Lite, Inc., and finished to match other framing sections.

2.8 FINISH HARDWARE

- A. Supplier: Refer to Section 08710 of these specifications for the Finish Hardware requirements for this project. Refer to approved Finish Hardware Schedule for items to be supplied to the door and frame manufacturer to install.
- B. Receive Hardware supplied in accordance with Section 08710, and Hardware Schedule, and coordinate with the Hardware requirements of this section. Report discrepancies (in writing) to the Architect immediately.
- C. Ship hardware, to be installed by manufacturer, to manufacturer with cartons marked with door numbers correlating with designation system used on shop drawings.
- D. Install all Hardware, except door holders at the fabrication plant. Remove only Hardware as required for final finishing or delivery to jobsite. Package and identify such Hardware and ship with doors and frames for installation at the project site.

2.9 FINISHES AND COLORS

- A. Fiberglass Reinforced Polyester Colors: As selected by Architect from manufacturer's complete range.
- B. Aluminum Framing:
  - 1. High-Performance Organic Coating: AA-C12C42R1x (Chemical Finish: cleaned with inhibited chemicals; Chemical Finish: chemical conversion coating, acid chromate-fluoride-phosphate pretreatment; Organic Coating: as specified below). Prepare, pre-treat, and apply coating to exposed metal surfaces to comply with coating and resin manufacturer's instruction.
  - 2. Fluorocarbon 3-Coat Coating System: Manufacturer's standard 3-coat thermo-cured system, composed of specially formulated inhibitive primer and fluorocarbon color coat, and clear fluorocarbon topcoat, with both color coat and clear topcoat containing not less than 70 percent polyvinylidene fluoride resin by weight; comply with AAMA 605.2.
  - 3. Color and Gloss: Custom color to match Architect's sample.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Comply with manufacturer's recommendations and specifications for the installation of the doors and frames.
- B. Set units plumb, level and true to line, without warp or rack of doors, frames or panels. Anchor securely in place. Separate aluminum, and other corrodible metal surfaces, from sources of

SECTION 082250  
FRP DOORS AND  
ALUMINUM FRAMES  
FOR FRP DOORS

corrosion or electrolytic action at points of contact with other materials, with bituminous coatings, or other means as approved by Architect.

- C. Set saddles in a bed of compound.
- D. Clean Aluminum surfaces promptly after installation of doors and frames, exercising care to avoid damage to the protective coating (if any). Remove excess glazing and sealant compounds, dirt and other substances.
- E. Provide protective treatment and other precautions required through the remainder of the construction period, to ensure that the doors and frames will be without damage or deterioration (other than normal weathering) at the time of acceptance.
- F. Adjusting: Adjust operating hardware to function properly, for smooth operation without binding, and for weathertight seal.
- G. Caulking: Refer to Section 07900 "Joint Sealants."

**\*\*END OF SECTION\*\***

PHENOLIC LOCKERS

PART 1 – GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes: Solid Phenolic Lockers, including custom Phone Lockers with integral USB charging ports.
- B. Related Sections:
  - 1. Division 06 Section "Rough Carpentry" for miscellaneous wood framing and blocking.

1.3 SUBMITTALS

- A. Submittals: Comply with procedures and quantities as indicated in Division 1 Submittal Procedure Section.
- B. Shop Drawings: Submit shop drawings indicating room sizes, layout, locker dimensions, material thickness, trim, hardware, finishes, locks, base, doors, accessories, and installation details.
- C. Product Data: Submit manufacturer's technical data for materials, fabrication, finishing, fastenings, hardware, and installation details.
- D. Samples: Submit samples of edge details, colors, patterns, finishes, and textures.
- E. Closeout Documents: Submit the following:
  - 1. Operation and maintenance data
  - 2. Warranty

1.4 QUALITY ASSURANCE

- A. Qualifications:
  - 1. Fabricator shall be capable of providing field service representation.
  - 2. Installer shall be approved by the manufacturer and be experienced in performing work of similar size and scope.
- B. Pre-installation Meeting: Conduct pre-installation meeting prior to installation to verify project requirements and conditions.

1.5 DELIVERY, STORAGE AND HANDLING

- A. Ordering: Comply with supplier's ordering and lead-time guidelines to avoid delays.
- B. Delivery: Deliver materials in the manufacturer's original protective packaging.
- C. Storage and Handling: Store materials in an enclosed shelter providing protection from damage, temperature, humidity, and exposure to the elements.

1.6 COORDINATION AND PROJECT CONDITIONS

- A. Field Measurements: Before material fabrication, verify actual field measurements and show actual measurements on shop drawings.
- B. Coordination: Coordinate field measurements with fabrication schedule and construction progress to avoid construction delays.

1.7 WARRANTY

- A. Submit executed copy of the Summit Lockers 20-year warranty against defects in material signed by an authorized representative of Summit Lockers.

PART 2 – PRODUCTS

2.1 SOLID PHENOLIC LOCKERS

- A. Basis of Design: Drawings and specifications are based on Summit Phenolic Lockers or approved equal from one of the following:
  - 1. ASI Storage Solutions
  - 2. Art Metal Products
  - 3. Hollman
  - 4. **Columbia Phenolic Lockers, a division of Partition Systems International of South Carolina \*\*ADD 02\*\***
- B. Locker Models: Refer to drawings for Locker Schedules, Sizes, Configurations and Locations.
  - 1. Lockers Single Tier Phenolic Locker, where scheduled and indicated.
  - 2. Lockers Three Tier Phenolic Locker, where scheduled and indicated.

2.2 MATERIALS

- A. Panel Material:
  - 1. Decorative papers impregnated with a melamine resin on faces with a clear protective overcoat and integrally compression molded within a core consisting of solid phenolic impregnated kraft papers.
  - 2. Fire Rating: Core or panel material shall meet fire Class B resistance per ASTM E84
- B. Doors & Ancillary Panels:
  - 1. Material: 1/2" (13mm) thick solid phenolic composite material.
  - 2. Corners: Eased edges
  - 3. Door Fastening: Blind fastening unless through bolts are requested
  - 4. Colors: As selected by Architect from manufacturer's full range of options. All phenolic panel edges are black.
- C. Locker Bodies

1. Exposed edges: Straight profile; eased edges to remove sharpness; machine polished and free from tooling imperfections.
2. Tops, bottoms, and intermediate shelves: 3/8" (9.5mm) thick solid phenolic composite material with ventilation holes.
3. Locker sides: 5/16" (8mm) thick solid phenolic composite material.
4. Locker backs: 1/4"+ (6mm) thick solid phenolic composite material.
5. Colors: Locker bodies are white. All phenolic panel edges are black.

D. Hardware

1. Hinges:
  - a. 180° Stainless Steel continuous hinge
2. Interior Side hooks:
  - a. Material: Stainless steel. Plastic and nylon hooks are not acceptable.
  - b. Two per opening for all openings 30" tall or greater.
3. Fasteners: All fasteners shall be stainless steel.
4. Door Identification Plates:
  - a. Material: Black plastic with reverse engraved numbers and surface mounted with permanent adhesive.
  - b. Fonts to be a minimum 1/2" high and up to four characters.
  - c. Numbering sequence to be provided by architect.
5. Door Locks:
  - a. Stainless steel hasp bar for customer supplied padlock

E. Ventilation

1. Vertical ventilation: Provide six 5/16" (8mm) diameter ventilation holes on tops, bottoms, and intermediate shelves. Provide three 5/16" (8mm) diameter ventilation holes on "Z" type intermediary shelves.
2. Horizontal ventilation: Provide ventilation around the edge of the door equal to at least 1.43 square inches of ventilation surface area per linear foot of door perimeter.

2.3 ACCESSORIES AND OPTIONS

A. Finished Locker Top:

1. Sloped top: 1/2" solid phenolic top color matched with lockers and installed at a 20° rise from front to back, using an extruded aluminum channel across the front.

B. Coat Rod: Stainless steel coat rod installed in locker openings greater than 30" H and 18"D.

C. Additional Door Ventilation:

1. Standard ventilation: Refer to section 2.2.F.

PART 3 – EXECUTION

3.1 EXAMINATION

- A. Examine site conditions before locker installation. Notify architect of unacceptable areas. Do not install lockers until unacceptable conditions have been corrected.

3.2 INSTALLATION

- A. Install lockers in locations as shown on shop drawings per manufacturer's instructions.
- B. Install lockers installed secured, plumb, level, square, and flush. Base by others must be flat and level.
- C. Install all required trim, fillers, end panels, and closures per manufacturer's instructions.
- D. Use hardware supplied or recommended by the manufacturer.
- E. Connect Phone Lockers USB charging ports to building electrical systems.
- F. Attach number plates to doors as indicated on shop drawings.
- G. Correct and/or replace damaged components as directed by architect.

3.3 ADJUSTMENT

- A. Adjust doors and locks for smooth operation without binding.
- B. Lubricate door hinges and locks per manufacturer's instructions.

3.4 CLEANING

- A. Clean all surfaces in accordance with manufacturer's instructions.
- B. Do not use abrasive cleaners.

**\*\*END OF SECTION\*\***

STORM DRAINAGE PIPING

|  |   |
|--|---|
| PART 1 - GENERAL .....                             | 1 |
| 1.1 RELATED DOCUMENTS .....                        | 1 |
| 1.2 PERFORMANCE REQUIREMENTS .....                 | 1 |
| 1.3 SYSTEMS DESCRIPTIONS .....                     | 1 |
| 1.4 SUBMITTALS .....                               | 1 |
| 1.5 QUALITY ASSURANCE .....                        | 2 |
| PART 2 - PRODUCTS .....                            | 2 |
| 2.1 MANUFACTURERS .....                            | 2 |
| 2.2 HUBLESS CAST-IRON SOIL PIPE AND FITTINGS ..... | 2 |
| 2.3 GALVANIZED STEEL PIPE AND FITTINGS .....       | 2 |
| 2.4 COPPER TUBE AND FITTINGS .....                 | 3 |
| 2.5 PVC PIPE AND FITTINGS .....                    | 3 |
| 2.6 SPECIAL PIPE FITTINGS .....                    | 3 |
| PART 3 - EXECUTION .....                           | 4 |
| 3.1 EXCAVATION .....                               | 4 |
| 3.2 PIPING SYSTEM INSTALLATION .....               | 4 |
| 3.3 JOINT CONSTRUCTION .....                       | 5 |
| 3.4 VALVE INSTALLATION .....                       | 5 |
| 3.5 HANGER AND SUPPORT INSTALLATION .....          | 5 |
| 3.6 CONNECTIONS .....                              | 6 |
| 3.7 FIELD QUALITY CONTROL .....                    | 6 |
| 3.8 CLEANING .....                                 | 7 |

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Related Sections include the following:
  - 1. Division 20 Section "Mechanical General Requirements."
  - 2. Division 20 Section "Basic Mechanical Materials and Methods."
  - 3. Division 22 Section "Drainage Piping Specialties."
  - 4. Division 22 Section "Sump Pumps."

1.2 PERFORMANCE REQUIREMENTS

1.3 SYSTEMS DESCRIPTIONS

- A. Storm drainage piping system materials are scheduled on the Drawing.

1.4 SUBMITTALS

- A. Product Data: For pipe, tube, fittings, and couplings.
- B. Shop Drawings:

- C. Field quality-control inspection and test reports.

1.5 QUALITY ASSURANCE

- A. Piping materials shall bear label, stamp, or other markings of specified testing agency.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. In other Part 2 articles where titles below introduce lists, the following requirements apply to product selection:
  - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the manufacturers specified.

2.2 HUBLESS CAST-IRON SOIL PIPE AND FITTINGS

- A. Pipe and Fittings: ASTM A 888 or CISPI 301.
- B. CISPI, Hubless-Piping Couplings:
  - 1. Manufacturers:
    - a. ANACO-Husky; McWane Plumbing Group.
    - b. Ferguson Enterprises, Inc.; ProFlo (Private labeled IDEAL-TRIDON).
    - c. IDEAL-TRIDON.
    - d. Mission Rubber Company; a division of MCP Industries, Inc.
    - e. Tyler Pipe; McWane Plumbing Group.
  - 2. Standards: CISPI 310.
  - 3. Description: NSF certified for compliance with CISPI 310. Stainless-steel corrugated shield with stainless-steel bands and tightening devices; and ASTM C 564, rubber sleeve with integral, center pipe stop.

2.3 GALVANIZED STEEL PIPE AND FITTINGS

- A. Galvanized Piping and fittings can be used in non-corrosive environments only.
- B. Galvanized Steel Pipe: ASTM A 53/A 53M, Type E or S, Grade A or B, Standard Weight or Schedule 40. Include ends matching joining method.
- C. Pressure Fittings:
  - 1. Steel Pipe Nipples: ASTM A 733, made of ASTM A 53/A 53M or ASTM A 106, Schedule 40, galvanized, seamless steel pipe. Include ends matching joining method.
  - 2. Malleable-Iron Unions: ASME B16.39; Class 150; hexagonal-stock body with ball-and-socket, metal-to-metal, bronze seating surface; and female threaded ends.
  - 3. Gray-Iron, Threaded Fittings: ASME B16.4, Class 125, galvanized, standard pattern.
  - 4. Cast-Iron Flanges: ASME B16.1, Class 125.

- D. Flanges: ASME 16.1, Class 125, cast iron.

#### 2.4 COPPER TUBE AND FITTINGS

- A. Copper Tube and Fittings can be used in corrosive environments.
- B. Copper DWV Tube: ASTM B 306, drainage tube, drawn temper.
  - 1. Copper Drainage Fittings: ASME B16.23, cast-copper or ASME B16.29, wrought-copper, solder-joint fittings.
- C. Hard Copper Tube: ASTM B 88, Type L, water tube, drawn temper.
  - 1. Copper Pressure Fittings: ASME B16.18, cast-copper-alloy or ASME B16.22, wrought-copper, solder-joint fittings. Furnish wrought-copper fittings if indicated.
  - 2. Copper Flanges: ASME B16.24, Class 150, cast copper with solder-joint end.
  - 3. Copper Unions: MSS SP-123, copper-alloy, hexagonal-stock body with ball-and-socket, metal-to-metal seating surfaces, and solder-joint or threaded ends.

#### 2.5 PVC PIPE AND FITTINGS

- A. Solid-Wall PVC Pipe: Schedule 40, ASTM D 2665, drain, waste, and vent.
  - 1. PVC Socket Fittings: ASTM D 2665, made to ASTM D 3311, drain, waste, and vent patterns and to fit Schedule 40 pipe.

#### 2.6 SPECIAL PIPE FITTINGS

- A. Flexible, Nonpressure Pipe Couplings: Comply with ASTM C 1173, elastomeric, sleeve-type, reducing or transition pattern. Include shear ring, ends of same sizes as piping to be joined, and corrosion-resistant-metal tension band and tightening mechanism on each end.
  - 1. Manufacturers:
    - a. Dallas Specialty & Mfg. Co.
    - b. Fernco, Inc.
    - c. Logan Clay Products Company (The).
    - d. Mission Rubber Co.
    - e. NDS, Inc.
    - f. Plastic Oddities, Inc.
  - 2. Sleeve Materials:
    - a. For Cast-Iron Soil Pipes: ASTM C 564, rubber.
    - b. For Plastic Pipes: ASTM F 477, elastomeric seal or ASTM D 5926, PVC.
    - c. For Dissimilar Pipes: ASTM D 5926, PVC or other material compatible with pipe materials being joined.
- B. Shielded Nonpressure Pipe Couplings: ASTM C 1460, elastomeric or rubber sleeve with full-length, corrosion-resistant outer shield and corrosion-resistant-metal tension band and tightening mechanism on each end.
  - 1. Manufacturers:

- a. Cascade Waterworks Mfg. Co.
  - b. Mission Rubber Co.
- C. Wall-Penetration Fittings: Compound, ductile-iron coupling fitting with sleeve and flexing sections for up to 20-degree deflection, gaskets, and restrained-joint ends complying with AWWA C110 or AWWA C153. Include AWWA C111, ductile-iron glands, rubber gaskets, and steel bolts.
- 1. Manufacturers:
    - a. SIGMA Corp.

### PART 3 - EXECUTION

#### 3.1 EXCAVATION

- A. Refer to Division 31 Section "Earthwork" for excavating, trenching, and backfilling.

#### 3.2 PIPING SYSTEM INSTALLATION

- A. Basic piping installation requirements are specified in Division 20 Section "Basic Mechanical Materials and Methods."
- B. Install cleanouts at grade and extend to where building storm drains connect to building storm sewers. Cleanouts are specified in Division 22 Section "Drainage Piping Specialties."
- C. Install cleanout fitting with closure plug inside the building in storm drainage force-main piping.
- D. Install cast-iron sleeve with water stop and mechanical sleeve seal at each service pipe penetration through foundation wall. Select number of interlocking rubber links required to make installation watertight. Sleeves and mechanical sleeve seals are specified in Division 20 Section "Basic Mechanical Materials and Methods."
- E. Make changes in direction for storm piping using appropriate branches, bends, and long-sweep bends. Do not change direction of flow more than 90 degrees. Use proper size of standard increasers and reducers if pipes of different sizes are connected. Reducing size of drainage piping in direction of flow is prohibited.
- F. Lay buried building drain piping beginning at low point of each system. Install true to grades and alignment indicated, with unbroken continuity of invert. Place hub ends of piping upstream. Install required gaskets according to manufacturer's written instructions for use of lubricants, cements, and other installation requirements. Maintain swab in piping and pull past each joint as completed.
- G. Install storm drainage piping at the following minimum slopes, unless otherwise indicated:
  - 1. Building Storm Drain: 1/8-inch per foot downward in direction of flow, unless otherwise noted.
  - 2. Horizontal Storm-Drainage Piping: 1/8-inch per foot downward in direction of flow, unless otherwise noted.
- H. Install force mains at elevations indicated.

- I. Sleeves are not required for cast-iron soil piping passing through concrete slabs-on-grade if slab is without membrane waterproofing.
- J. Do not enclose, cover, or put piping into operation until it is inspected and approved by authorities having jurisdiction.
- K. Install PVC storm drainage piping according to ASTM D 2665.
- L. Install underground PVC storm drainage piping according to ASTM D 2321.

### 3.3 JOINT CONSTRUCTION

- A. Basic piping joint construction requirements are specified in Division 20 Section "Basic Mechanical Materials and Methods."
- B. Hubless Cast-Iron Soil Piping Coupled Joints: Join according to CISPI 310 and CISPI's "Cast Iron Soil Pipe and Fittings Handbook" for hubless-coupling joints.
- C. PVC Nonpressure Piping Joints: Join piping according to ASTM D 2665.

### 3.4 VALVE INSTALLATION

- A. General valve installation requirements are specified in Division 20 Section "Valves."
- B. Shutoff Valves: Install shutoff valve on each sump pump discharge.
  - 1. Install gate or full-port ball valve for piping NPS 2 and smaller.
- C. Check Valves: Install swing check valve, between pump and shutoff valve, on each sump pump discharge.

### 3.5 HANGER AND SUPPORT INSTALLATION

- A. Pipe hangers and supports are specified in Division 20 Section "Hangers and Supports." Install the following:
  - 1. Vertical Piping: MSS Type 8 or Type 42, clamps.
  - 2. Individual, Straight, Horizontal Piping Runs: According to the following:
    - a. 100 Feet and Less: MSS Type 1, adjustable, steel clevis hangers.
    - b. Longer Than 100 Feet: MSS Type 43, adjustable roller hangers.
    - c. Longer Than 100 Feet, if Indicated: MSS Type 49, spring cushion rolls.
  - 3. Multiple, Straight, Horizontal Piping Runs 100 Feet or Longer: MSS Type 44, pipe rolls. Support pipe rolls on trapeze.
  - 4. Base of Vertical Piping: MSS Type 52, spring hangers.
- B. Install supports according to Division 20 Section "Hangers and Supports."
- C. Support vertical piping and tubing at base and at each floor.
- D. Rod diameter may be reduced 1 size for double-rod hangers, with 3/8-inch minimum rods.

- E. Install hangers for steel piping with the following maximum horizontal spacing and minimum rod diameters:
  - 1. NPS 2: 10 feet with 3/8-inch rod.
- F. Install supports for vertical steel piping every 15 feet.
- G. Install hangers for copper tubing with the following maximum horizontal spacing and minimum rod diameters:
  - 1. NPS 2: 96 inches with 3/8-inch rod.
- H. Install supports for vertical copper tubing every 10 feet.
- I. Support piping and tubing not listed above according to MSS SP-69 and manufacturer's written instructions.

### 3.6 CONNECTIONS

- A. Drawings indicate general arrangement of piping, fittings, and specialties.
- B. Connect interior storm drainage piping to exterior storm drainage piping. Use transition fitting to join dissimilar piping materials.
- C. Connect force-main piping to the following:
  - 1. Storm Sewer: To exterior force main or storm manhole.
  - 2. Sump Pumps: To sump pump discharge.

### 3.7 FIELD QUALITY CONTROL

- A. During installation, notify authorities having jurisdiction at least 24 hours before inspection must be made. Perform tests specified below in presence of authorities having jurisdiction.
  - 1. Roughing-in Inspection: Arrange for inspection of piping before concealing or closing-in after roughing-in.
  - 2. Final Inspection: Arrange for final inspection by authorities having jurisdiction to observe tests specified below and to ensure compliance with requirements.
- B. Reinspection: If authorities having jurisdiction find that piping will not pass test or inspection, make required corrections and arrange for reinspection.
- C. Reports: Prepare inspection reports and have them signed by authorities having jurisdiction.
- D. Test force-main piping according to procedures of authorities having jurisdiction or, in absence of published procedures, as follows:
  - 1. Leave uncovered and unconcealed new, altered, extended, or replaced force-main piping until it has been tested and approved. Expose work that was covered or concealed before it was tested.
  - 2. Cap and subject piping to static-water pressure of 150 psig, without exceeding pressure rating of piping system materials. Isolate test source and allow to stand for four hours.

Leaks and loss in test pressure constitute defects that must be repaired.

3. Repair leaks and defects with new materials and retest piping, or portion thereof, until satisfactory results are obtained.
4. Prepare reports for tests and required corrective action.

3.8 CLEANING

- A. Clean interior of piping. Remove dirt and debris as work progresses.
- B. Protect drains during remainder of construction period to avoid clogging with dirt and debris and to prevent damage from traffic and construction work.
- C. Place plugs in ends of uncompleted piping at end of day and when work stops.

**\*\*END OF SECTION\*\***

SUMP PUMPS

|   |   |
|---|---|
| PART 1 - GENERAL .....                    | 1 |
| 1.1 RELATED DOCUMENTS .....               | 1 |
| 1.2 SUMMARY .....                         | 1 |
| 1.3 SUBMITTALS .....                      | 1 |
| 1.4 QUALITY ASSURANCE .....               | 1 |
| 1.5 DELIVERY, STORAGE, AND HANDLING ..... | 2 |
| PART 2 - PRODUCTS .....                   | 2 |
| 2.1 MANUFACTURERS .....                   | 2 |
| 2.2 SUBMERSIBLE SUMP PUMPS .....          | 2 |
| 2.3 SUMP PUMP BASINS .....                | 3 |
| PART 3 - EXECUTION .....                  | 4 |
| 3.1 EXAMINATION .....                     | 4 |
| 3.2 SUMP PUMP INSTALLATION .....          | 4 |
| 3.3 CONNECTIONS .....                     | 4 |
| 3.4 STARTUP SERVICE .....                 | 5 |
| 3.5 DEMONSTRATION .....                   | 5 |

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Related Sections include the following:
  - 1. Division 20 Section "Mechanical General Requirements."
  - 2. Division 20 Section "Basic Mechanical Materials and Methods."

1.2 SUMMARY

- A. This Section includes sump pumps and accessories, inside the building, for building storm drainage systems.

1.3 SUBMITTALS

- A. Product Data: For each type and size of sump pump specified, include certified performance curves with operating points plotted on curves, rated capacities of selected models, furnished specialties, and accessories.
- B. Shop Drawings: Diagram power, signal, and control wiring.
- C. Operation and Maintenance Data: For each sump pump to include in operation and maintenance manuals.

1.4 QUALITY ASSURANCE

- A. Product Options: Drawings indicate size, profiles, and dimensional requirements of sump pumps and are based on the specific system indicated. Refer to Division 01 Section "Product Requirements."

- B. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by an NRTL acceptable to authorities having jurisdiction, and marked for intended use.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Retain shipping flange protective covers and protective coatings during storage.
- B. Protect bearings and couplings against damage.
- C. Comply with pump manufacturer's written rigging instructions for handling.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. In other Part 2 articles where titles below introduce lists, the following requirements apply to product selection:
  - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the manufacturers specified.

2.2 SUBMERSIBLE SUMP PUMPS

- A. Manufacturers:
  - 1. ABS Pumps, Inc.
  - 2. Bell & Gossett; Xylem Inc.
  - 3. Crane Pumps and Systems; Barnes.
  - 4. EBARA International Corporation; Standard Pump Division.
  - 5. Goulds Pumps; Xylem Inc.
  - 6. Gorman-Rupp Company (The).
  - 7. Grundfos Pumps Corporation.
  - 8. Hydromatic.
  - 9. Little Giant Pump Co.
  - 10. Metropolitan Industries, Inc.
  - 11. Weil Pump Company, Inc.
  - 12. Zoeller Company.
  - 13. Liberty Pumps.
- B. Description: Factory-assembled and -tested, simplex, single-stage, centrifugal, end-suction, submersible, direct-connected sump pumps complying with UL 778 and Hydraulic Institute

HI 1.1-1.2 and HI 1.3 for submersible sump pumps.

- C. Casing: Stainless steel; with stainless-steel inlet strainer, legs that elevate pump to permit flow into impeller, and vertical discharge with companion flange suitable for piping connection.
- D. Impeller: stainless steel; statically and dynamically balanced, semi-open non-clog design, overhung, single suction, keyed and secured to shaft.
- E. Pump and Motor Shaft: Stainless steel, with factory-sealed, grease-lubricated ball bearings and double-mechanical seals.
- F. Motor: Hermetically sealed, capacitor-start type, with built-in overload protection; three-conductor waterproof power cable of length required, and with grounding plug and cable-sealing assembly for connection at pump. Comply with requirements in Division 20 Section "Motors."
- G. Pump Discharge Piping: Factory or field fabricated. Refer to Division 22 Section "Storm Drainage Piping."
- H. Basin Cover: Cast iron or steel with bituminous coating and strong enough to support controls. See Part 2 "Sump Pump Basins Article for other requirements.
- I. Controls:
  - 1. Mount controls in NEMA 250, Type 4X enclosure. Controls shall include: Fused disconnect switches and combination magnetic starters with overload protection for each phase to protect against single phasing. Three phase units shall include control transformer and control circuit fuse.
    - a. Minimum SCCR according to UL 508 shall be as required by electrical power distribution system, but not less than 10,000 A.
      - 1) NEMA KS 1, heavy-duty, fusible switch with rejection-type fuse clips rated for fuses. Select and size fuses to provide Type 2 protection according to IEC 60947-4-1.
  - 2. Station shall be furnished with three, single pole, normally-open NON-mercury mechanical float switches with 20 ft. cords, clamps, cord grips, and fasteners for pump off/pump on/high-water-alarm operation. The high-water-alarm switch shall be mounted as indicated on the Drawings. System shall be complete with cover mounting bracket. (1-inch diameter support pole by Contractor.)
  - 3. Provide high water alarm switch, complete with actuating mechanism for operation on an electric circuit other than the motor circuit. The switch shall be designed to operate indicated alarm device(s) and one set of spare contacts whenever a predetermined high-water level is reached in the sump. Provide alarm pilot light and alarm bell with silence switch. Mount controls on pedestal on the sump cover plate.

### 2.3 SUMP PUMP BASINS

- A. Manufacturer: Sump pump and basin are to be provided by the same manufacturer.
- B. Description: Factory fabricated basin with sump, pipe connections, and separate cover.
- C. Sump: Fabricate watertight, with sidewall openings for pipe connections.

1. Material: Fiberglass.
  2. Reinforcement: Mounting plates for pumps, fittings, and accessories.
  3. Anchor Flange: Same material as or compatible with sump, cast in or attached to sump, in location and of size required to anchor basin in concrete slab.
- D. Cover: Fabricate with openings having gaskets, seals, and bushings, for access to pumps, pump shafts, control rods, discharge piping, vent connections, and power cables.
1. Material: Cast iron or steel with bituminous coating.
  2. Reinforcement: Steel or cast iron, capable of supporting foot traffic for basins installed in foot-traffic areas.
- E. Capacity and Characteristics:
1. Refer to Drawings for capacity and characteristics.

### PART 3 - EXECUTION

#### 3.1 EXAMINATION

- A. Examine roughing-in of plumbing piping to verify actual locations of storm drainage piping connections before sump pump installation.

#### 3.2 SUMP PUMP INSTALLATION

- A. Excavating, trenching, and backfilling are specified in Division 31 Section "Earthwork."
- B. Install sump pumps according to applicable requirements in Hydraulic Institute HI 1.4.
- C. Install pumps and arrange to provide access for maintenance including removal of motors, impellers, couplings, and accessories.
- D. Set submersible sump pumps on basin floor. Make direct connections to storm drainage piping.
- E. Install sump pump basins and connect to drainage piping. Brace interior of basins according to manufacturer's written instructions to prevent distortion or collapse during concrete placement. Set basin cover and fasten to basin top flange. Install cover so top surface is flush with finished floor.
- F. Install submersible unit basins on floor or concrete base unless recessed installation is indicated. Make direct connections to storm drainage piping.
- G. Support piping so weight of piping is not supported by pumps.

#### 3.3 CONNECTIONS

- A. Piping installation requirements are specified in Division 22 Section "Storm Drainage Piping." Drawings indicate general arrangement of piping, fittings, and specialties.
- B. Install piping adjacent to sump pumps to allow service and maintenance.

- C. Connect storm drainage piping to pumps. Install discharge piping equal to pump discharge connection size. If pump discharge connection size is different from storm drainage piping size, provide transition from pump discharge piping size to storm drainage piping size. Refer to Division 22 Section "Storm Drainage Piping."
  - 1. Install check and shutoff valves on discharge piping from each pump. Install unions on pumps having threaded pipe connections. Install valves same size as connected piping. Refer to Division 20 Section "Valves" for general-duty valves for drainage piping.
- D. Ground equipment according to Division 26 Section "Grounding and Bonding."
- E. Connect wiring according to Division 26 Section "Conductors and Cables."




### 3.4 STARTUP SERVICE

- A. Engage a factory-authorized service representative to perform startup service.
  - 1. Complete installation and startup checks according to manufacturer's written instructions.
  - 2. Verify bearing lubrication.
  - 3. Disconnect couplings and check motors for proper direction of rotation.
  - 4. Verify that each pump is free to rotate by hand. If pump is bound or drags, do not operate until cause of trouble is determined and corrected.
- B. Start pumps without exceeding safe motor power:
  - 1. Start motors.
  - 2. Open discharge valves slowly.
  - 3. Check general mechanical operation of pumps and motors.
- C. Test and adjust controls and safeties.
- D. Remove and replace damaged and malfunctioning components.
  - 1. Pump Controls: Set pump controls for automatic start, stop, and alarm operation as required for system application.
  - 2. Set field-adjustable switches and circuit-breaker trip ranges as indicated, or if not indicated, for normal operation.




### 3.5 DEMONSTRATION

- A. Engage a factory-authorized service representative to train Owner's maintenance personnel to adjust, operate, and maintain controls and pumps. Refer to Division 20 Section "Mechanical General Requirements."

\*\*END OF SECTION\*\*



- UTILITY NOTES**
- STORM SEWER NOTED AS 6" SHALL BE PVC SCHEDULE 40. STORM SEWER GREATER THAN 6" THROUGH 10" SHALL BE PVC SDR 26. STORM SEWER NOTED AS 6" THROUGH 10" SHALL BE PVC SDR 26. STORM SEWER NOTED AS 6" THROUGH 10" SHALL BE PVC SDR 26.
  - SANITARY SEWER 8" AND LARGER SHALL BE PVC TRUSS PIPE. 6" SANITARY LEADS SHALL BE SOLID WALL PVC, SDR 23.5.
  - WATER MAIN SHALL BE CLASS 50 DUCTILE IRON. WATER MAINS SHALL BE LEAKAGE AND PRESSURE TESTED IN ACCORDANCE WITH AWWA STANDARD C600. WATER MAINS SHALL BE INSPECTED IN ACCORDANCE WITH AWWA STANDARD C601 PRIOR TO BEING PUT INTO SERVICE.
  - ALL UTILITIES REMOVED THAT FALL WITHIN A 1'-0" INFLUENCE OF PAVEMENT AREAS SHALL BE BACKFILLED WITH CLASS 2 SAND AND COMPACTED TO 95% OF MAXIMUM DENSITY.
  - ALL WATER MAINS SHALL BE BURIED WITH 5' OF COVER FROM PROPOSED GRADES. USE 22.5' BENDS TO LOWER WATER MAIN WHEN NOTED AT UTILITY CROSSING.
  - ALL UTILITIES SHALL BE INSTALLED IN ACCORDANCE WITH THE STANDARDS AND SPECIFICATIONS OF THE CITY OF DEARBORN.
  - ALL UTILITIES SHALL BE INSTALLED ON CLASS "B" BEDDING OR BETTER.
  - SIZE OF STORM SEWER STRUCTURES SHALL BE AS NOTED ON THE PLANS.
  - ALL PROPOSED STORM SEWER CATCH BASINS AND INLET STRUCTURES SHALL HAVE A 2" MINIMUM SUMP.
  - UNLESS OTHERWISE NOTED, PROPOSED CASTINGS SHALL BE:  
FIELD CATCH BASINS - EAW 5008 - 10" (FRAMES WITH CURB BOXES WILL NOT BE ALLOWED)  
FIELD CATCH BASINS - EAW 1040 - 10"  
STORM MANHOLES - EAW 1040 - 10"
  - LOCATIONS OF LIGHT POLES, IF SHOWN ON THESE DRAWINGS, MAY BE APPROXIMATE. CONFIRM EXACT LOCATION (I.E. CURB BORDERS, SIDEWALK OFFSETS, ETC.) PRIOR TO STAKING AND CONSTRUCTION. REFER TO SITE ELECTRICAL PLAN FOR DETAILS AND COORDINATE WITH ELECTRICAL ENGINEER, ARCHITECT, AND CIVIL ENGINEER TO DETERMINE PROPER PLACEMENT.
  - WHERE THESE PLANS DIFFER FROM THE STANDARD DETAILS OR STANDARD SPECIFICATIONS OF THE COMMUNITY, THE COMMUNITY REQUIREMENTS SHALL GOVERN.




**UTILITY CROSSING TABLE**

| NO. | UTILITY      | PROPOSED DEPTH         | EXISTING DEPTH                        | CLEARANCE         | NOTES                              |
|-----|--------------|------------------------|---------------------------------------|-------------------|------------------------------------|
| 1   | SAN/STW XING | PROP IF SAN TIP 590.00 | EX. 12" STW TIP 590.33 (FIELD VERIFY) | CLEARANCE = 0.27' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 2   | SAN/STW XING | PROP IF SAN TIP 590.30 | EX. 10" STW TIP 590.77 (FIELD VERIFY) | CLEARANCE = 1.41' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 3   | SAN/STW XING | PROP IF SAN TIP 591.07 | EX. 12" STW TIP 591.22 (FIELD VERIFY) | CLEARANCE = 1.15' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 4   | SAN/STW XING | PROP IF SAN TIP 591.13 | EX. 12" STW TIP 591.13 (FIELD VERIFY) | CLEARANCE = 0.00' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 5   | SAN/STW XING | PROP IF SAN TIP 592.02 | EX. 12" STW TIP 592.02 (FIELD VERIFY) | CLEARANCE = 0.00' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 6   | SAN/STW XING | PROP IF SAN TIP 592.13 | EX. 12" STW TIP 592.13 (FIELD VERIFY) | CLEARANCE = 0.00' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 7   | SAN/STW XING | PROP IF SAN TIP 592.30 | EX. 12" STW TIP 592.30 (FIELD VERIFY) | CLEARANCE = 0.00' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 8   | SAN/STW XING | PROP IF SAN TIP 592.33 | EX. 12" STW TIP 592.33 (FIELD VERIFY) | CLEARANCE = 0.00' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 9   | SAN/STW XING | PROP IF SAN TIP 592.33 | EX. 12" STW TIP 592.33 (FIELD VERIFY) | CLEARANCE = 0.00' | NOTIFY ENGINEER IF CONFLICT OCCURS |
| 10  | SAN/STW XING | PROP IF SAN TIP 592.33 | EX. 12" STW TIP 592.33 (FIELD VERIFY) | CLEARANCE = 0.00' | NOTIFY ENGINEER IF CONFLICT OCCURS |

NOTE: EXISTING STORM SEWER INVERT ELEVATIONS ARE ASSUMED BASED ON ASSUMED PIPE SLOPES. CONTRACTOR SHALL CONFIRM EXACT DEPTHS PRIOR TO THE START OF ANY PROPOSED UNDERGROUND UTILITY INSTALLATION AND SHALL NOTIFY THE ENGINEER IF ANY CONFLICTS EXIST.


**RESTORATION NOTE**  
RESTORE ALL DISTURBED LAWN AREAS WITH 4" OF CLEAN TOPSOIL AND SEED MIX USING NONWOOL BLENDING. SEE PROFORMA. REPAIRS, SIDE DRESSING AND FERTILIZER PLACE IN ALL SEEDING AREAS ON SLOPES IN EXCESS OF 10% HORIZONTAL TO 1 VERTICAL PLACE NORTH AMERICAN GREEN DSS30 MATCH BLANKET IMMEDIATELY AFTER SEEDING. USE METAL STAPLES PER MANUFACTURER'S RECOMMENDATIONS TO HOLD MATTING IN PLACE.

**RIM ADJUSTMENT NOTE:**  
REMOVE EXISTING CASTING COVER AND ADJUSTMENT MATERIALS FROM DRAINAGE STRUCTURE. SALVAGE CASTING AND COVER FOR REINSTALLATION AND PROVIDE NEW ADJUSTMENT BRICK/BLOCK/ANVILS. RENEWAL ACCORDING TO STANDARD DETAILS OF INCLCDED. PROTECT EXISTING UTILITY STRUCTURE TO REMAIN.



**GRADING NOTE**  
1. PROPOSED GRADES ARE SOMETIMES BASED ON AN INTERPOLATION OF DATA SHOWN ON THE TOPOGRAPHIC SURVEY. THIS INTERPOLATED DATA IS APPROXIMATE AND COULD DIFFER SLIGHTLY BASED ON THE ACCURACY OF THE SURVEY. CONTRACTOR SHALL VERIFY THAT THE PROPOSED GRADES SHOWN ON THIS PLAN WILL NOT CREATE A STANDING WATER CONDITION (I.E. A LOW SPOT OR PAVED SLOPES LESS THAN 1% OR AN UNSAFE CONDITION WITH SLOPES IN EXCESS OF 5% CONTRACTOR SHALL ADVISE ENGINEER IMMEDIATELY IF THEY BELIEVE THAT ONE OF THESE SITUATIONS WILL OCCUR BASED ON THE PROPOSED GRADES.

2. CONTRACTOR IS RESPONSIBLE FOR CONTROLLING STORMWATER RUNOFF DURING CONSTRUCTION OPERATIONS. OF PARTICULAR CONCERN WILL BE THE TIME PERIOD AFTER THE SITE HAS BEEN STORMED AND NOT YET RESTORED. BUILT UPON OR PAVED. CONTRACTOR MUST INSTALL OR CONSTRUCT APPROPRIATE TEMPORARY MEASURES TO PROTECT ADJACENT PROPERTIES.



**TMP ARCHITECTURE**

REGISTRATION SEAL

CONSULTANT

PROJECT TITLE  
**Ford Woods Park Pool**

City of Dearborn

DRAWING TITLE  
**Site Engineering Plan**

ISSUE DATES

| DATE       | ISSUED FOR:    |
|------------|----------------|
| 11-16-2017 | ADDENDUM NO. 2 |
| 10-25-2017 | BIDS           |
| 09-27-2017 | OWNER REVIEW   |

DATE: ISSUED FOR:

DRAWN: JRE

CHECKED: TJS

APPROVED: TJS


PROJECT NO.  
**TMP - 17071**  
**SDA - NP17041**

DRAWING NO.  
**C1.3**

3 WORKING DAYS BEFORE YOU DIG CALL MISS DIG. 1-800-482-7171



THE FOLLOWING DIMENSION EQUALS ONE INCH WHEN PRINTED TO SCALE.



**UNDERGROUND PLUMBING PLAN**  
SCALE: 1/8" = 1' - 0"

**PLUMBING GENERAL NOTES:**

1. THESE DRAWINGS ARE DIAGRAMMATIC, AND REPRESENT THE GENERAL INTENT AND ARRANGEMENT OF SYSTEMS. THEY ARE NOT TO BE CONSIDERED FABRICATION/COORDINATION/SHOP DRAWINGS. COORDINATION WITH OTHER TRADES IS REQUIRED. PROVIDE THE ADDITIONAL FITTINGS AND OFFSETS THAT WILL BE REQUIRED TO COMPLETE EACH SYSTEM AND TO AVOID INTERFERENCES WITH ALL OTHER SYSTEMS INCLUDING THE STRUCTURE, SHEET METAL, OTHER PIPING SYSTEMS, ELECTRICAL CONDUITS, BUS DUCTS, CABLE TRAY, LIGHT FIXTURES, ETC. AND/OR OTHER SPACE CONSTRAINTS.
2. INSTALL SYSTEMS SUCH THAT REQUIRED CLEARANCE AND SERVICE ACCESS SPACE IS PROVIDED AROUND ALL MECHANICAL AND ELECTRICAL EQUIPMENT, AND AROUND ANY COMPONENTS WHICH REQUIRE SERVICE ACCESS.
3. PIPING SHALL NOT BE INSTALLED ABOVE ELECTRICAL TRANSFORMERS, SWITCHBOARDS, PANELBOARDS OR MOTOR CONTROL CENTERS.
4. COORDINATE AND PROVIDE ACCESS DOORS WITHIN INACCESSIBLE CEILING, SHAFT, AND CHASE AREAS FOR ALL COMPONENTS WHICH REQUIRE SERVICE ACCESS. REFER TO ARCHITECTURAL DRAWINGS FOR CEILING TYPES.
5. PROVIDE SUPPLEMENTARY STEEL AS REQUIRED FOR THE PROPER SUPPORT OF ALL SYSTEMS.
6. REFER TO ARCHITECTURAL PLANS FOR DIMENSIONED LOCATIONS OF PLUMBING FIXTURES.
7. HOT AND COLD WATER PIPING RUN-OUTS TO LAVATORIES AND SINKS SHALL BE 1/2" UNLESS OTHERWISE NOTED.
8. PLUMBING VENT PIPING THROUGH ROOF SHALL BE LOCATED A MINIMUM OF 10'-0" FROM ANY FRESH AIR INTAKE LOCATION AND A MINIMUM OF 18" CLEAR FROM THE INSIDE FACE OF PARAPET.
9. PROVIDE CODE REQUIRED CLEARANCE FOR ALL CLEANOUTS INSTALLED IN SANITARY WASTE AND VENT PIPING.
10. MINIMUM UNDERGROUND PIPE SIZE SHALL BE 3".
11. WATER SERVICE ENTRANCE PIPING SHALL BE BURIED WITH DEPTH OF COVER OVER TOP OF PIPE OF AT LEAST 18" OR WITH TOP OF PIPE AT LEAST 12" BELOW LEVEL OF MAXIMUM FROST PENETRATION, OR AS REQUIRED BY AUTHORITIES HAVING JURISDICTION, WHICHEVER IS DEEPEST.

**CONSTRUCTION KEY NOTES:**

1. SLOPE DOMESTIC WATER PIPING TO SERVICE SINK IN JANITOR CLOSET.
2. CONNECT HW, CW, AND VENT PIPING TO LAVS.
3. CONNECT HW, CW, AND VENT PIPING TO SINK.
4. PROVIDE WET PIPE SPRINKLER SYSTEM PER NFPA 13.
5. ROUTE 1 1/4" CW AND 1 1/4" HW TO MIXING VALVE LOCATED ON WALL ABOVE UNIT.
6. PROVIDE DOUBLE CHECK VALVE ASSEMBLY FOR FIRE PROTECTION SYSTEM. ROUTE F PIPING TO CHLORINE AND ACID ROOM AND PROVIDE SPRINKLER HEADS IN EACH.
7. ROUTE 2 1/2" CW TO FILL STATION LOCATED ON THE EAST WALL. PROVIDE PIPING CONFIGURATION AS OUTLINED ON SHEET SP4.2, DETAIL 10.
8. LOCATE SUMP PUMP CONTROL PANEL ON UNI-STRUT RACK, PROVIDE REQUIRED CLEARANCE IN FRONT AND TOP OF PANEL.



REGISTRATION SEAL

CONSULTANT

PROJECT TITLE  
**Ford Woods Park Pool**

City of Dearborn

DRAWING TITLE  
**UNDERGROUND PLUMBING PLAN**

ISSUE DATES

|            |                |
|------------|----------------|
| 11-16-2017 | ADDENDUM NO. 2 |
| 10-25-2017 | BIDS           |
| 09-27-2017 | OWNER REVIEW   |

|               |             |
|---------------|-------------|
| DATE:         | ISSUED FOR: |
| DRAWN: JTH    |             |
| CHECKED: DAC  |             |
| APPROVED: DAC |             |


PROJECT NO.

**17071**


DRAWING NO.

**M2.0**


THE FOLLOWING DIMENSION EQUALS ONE INCH WHEN PRINTED TO SCALE.



**1 LOCKER ROOM SECTION**  
SCALE: 1/8" = 1' - 0"



**2 STORAGE ROOM SECTION**  
SCALE: 1/8" = 1' - 0"



**PLUMBING AND FIRE PROTECTION PLAN**  
SCALE: 1/8" = 1' - 0"

**FIRE PROTECTION GENERAL NOTES:**

1. THESE DRAWINGS ARE DIAGRAMMATIC, AND REPRESENT THE GENERAL INTENT AND ARRANGEMENT OF SYSTEMS. THEY ARE NOT TO BE CONSIDERED FABRICATION/COORDINATION/SHOP DRAWINGS. COORDINATION WITH OTHER TRADES IS REQUIRED. PROVIDE THE ADDITIONAL FITTINGS AND OFFSETS THAT WILL BE REQUIRED TO COMPLETE EACH SYSTEM AND TO AVOID INTERFERENCES WITH ALL OTHER SYSTEMS INCLUDING THE STRUCTURE, SHEET METAL, OTHER PIPING SYSTEMS, ELECTRICAL CONDUITS, BUS DUCTS, CABLE TRAY, LIGHT FIXTURES, ETC. AND/OR OTHER SPACE CONSTRAINTS.
2. INSTALL SYSTEMS SUCH THAT REQUIRED CLEARANCE AND SERVICE ACCESS SPACE IS PROVIDED AROUND ALL MECHANICAL AND ELECTRICAL EQUIPMENT, AND AROUND ANY COMPONENTS WHICH REQUIRE SERVICE ACCESS.
3. NO SPRINKLER PIPING SHALL BE ROUTED THROUGH ELECTRICAL EQUIPMENT ROOMS, TELECOMMUNICATION EQUIPMENT ROOMS, ELEVATOR EQUIPMENT ROOMS OR SIMILAR ROOMS. ONLY SPRINKLER PIPING SERVING SPRINKLER HEADS IN THOSE ROOMS SHALL BE ALLOWED.
4. PIPING SHALL NOT BE INSTALLED ABOVE ELECTRICAL TRANSFORMERS, SWITCHBOARDS, PANELBOARDS OR MOTOR CONTROL CENTERS.
5. MINIMUM RUN-OUT PIPE SIZE TO SPRINKLER HEADS SHALL BE 1".

**PLUMBING GENERAL NOTES:**

1. THESE DRAWINGS ARE DIAGRAMMATIC, AND REPRESENT THE GENERAL INTENT AND ARRANGEMENT OF SYSTEMS. THEY ARE NOT TO BE CONSIDERED FABRICATION/COORDINATION/SHOP DRAWINGS. COORDINATION WITH OTHER TRADES IS REQUIRED. PROVIDE THE ADDITIONAL FITTINGS AND OFFSETS THAT WILL BE REQUIRED TO COMPLETE EACH SYSTEM AND TO AVOID INTERFERENCES WITH ALL OTHER SYSTEMS INCLUDING THE STRUCTURE, SHEET METAL, OTHER PIPING SYSTEMS, ELECTRICAL CONDUITS, BUS DUCTS, CABLE TRAY, LIGHT FIXTURES, ETC. AND/OR OTHER SPACE CONSTRAINTS.
2. INSTALL SYSTEMS SUCH THAT REQUIRED CLEARANCE AND SERVICE ACCESS SPACE IS PROVIDED AROUND ALL MECHANICAL AND ELECTRICAL EQUIPMENT, AND AROUND ANY COMPONENTS WHICH REQUIRE SERVICE ACCESS.
3. PIPING SHALL NOT BE INSTALLED ABOVE ELECTRICAL TRANSFORMERS, SWITCHBOARDS, PANELBOARDS OR MOTOR CONTROL CENTERS.
4. COORDINATE AND PROVIDE ACCESS DOORS WITHIN INACCESSIBLE CEILING, SHAFT, AND CHASE AREAS FOR ALL COMPONENTS WHICH REQUIRE SERVICE ACCESS. REFER TO ARCHITECTURAL DRAWINGS FOR CEILING TYPES.
5. PROVIDE SUPPLEMENTARY STEEL AS REQUIRED FOR THE PROPER SUPPORT OF ALL SYSTEMS.
6. REFER TO ARCHITECTURAL PLANS FOR DIMENSIONED LOCATIONS OF PLUMBING FIXTURES.
7. HOT AND COLD WATER PIPING RUN-OUTS TO LAVATORIES AND SINKS SHALL BE 1/2" UNLESS OTHERWISE NOTED.
8. PLUMBING VENT PIPING THROUGH ROOF SHALL BE LOCATED A MINIMUM OF 10'-0" FROM ANY FRESH AIR INTAKE LOCATION AND A MINIMUM OF 18" CLEAR FROM THE INSIDE FACE OF PARAPET.
9. PROVIDE CODE REQUIRED CLEARANCE FOR ALL CLEANOUTS INSTALLED IN SANITARY WASTE AND VENT PIPING.
10. MINIMUM UNDERGROUND PIPE SIZE SHALL BE 3".
11. WATER SERVICE ENTRANCE PIPING SHALL BE BURIED WITH DEPTH OF COVER OVER TOP OF PIPE OF AT LEAST 12" OR WITH TOP OF PIPE AT LEAST 12" BELOW LEVEL OF MAXIMUM FROST PENETRATION, OR AS REQUIRED BY AUTHORITIES HAVING JURISDICTION, WHICHEVER IS DEEPEST.

**CONSTRUCTION KEY NOTES:**

1. SLOPE DOMESTIC WATER PIPING TO SERVICE SINK IN JANITOR CLOSET.
2. CONNECT HW, CW, AND VENT PIPING TO LAVS.
3. CONNECT HW, CW, AND VENT PIPING TO SINK.
4. PROVIDE WET PIPE SPRINKLER SYSTEM PER NFPA 13.
5. ROUTE 1 1/4 CW AND 1 1/4 HW TO MIXING VALVE LOCATED ON WALL ABOVE UNIT.
6. PROVIDE DOUBLE CHECK VALVE ASSEMBLY FOR FIRE PROTECTION SYSTEM. ROUTE F PIPING TO CHLORINE AND ACID ROOM AND PROVIDE SPRINKLER HEADS IN EACH.
7. ROUTE 2 1/2 CW TO FILL STATION LOCATED ON THE EAST WALL. PROVIDE PIPING CONFIGURATION AS OUTLINED ON SHEET SP4.2, DETAIL 10.
8. LOCATE SUMP PUMP CONTROL PANEL ON UNI-STRUT RACK, PROVIDE REQUIRED CLEARANCE IN FRONT AND TOP OF PANEL.



REGISTRATION SEAL

CONSULTANT

PROJECT TITLE  
**Ford Woods Park Pool**

City of Dearborn

DRAWING TITLE  
**PLUMBING PLAN**

ISSUE DATES

|            |                |
|------------|----------------|
| 11-16-2017 | ADDENDUM NO. 2 |
| 10-25-2017 | BIDS           |
| 09-27-2017 | OWNER REVIEW   |

|              |             |
|--------------|-------------|
| DATE:        | ISSUED FOR: |
| DRAWN JTH    |             |
| CHECKED DAC  |             |
| APPROVED DAC |             |

PROJECT NO.

**17071**

DRAWING NO.

**M2.1**







REGISTRATION SEAL

CONSULTANT

PROJECT TITLE  
Ford Woods  
Park Pool

City of Dearborn

DRAWING TITLE  
MECHANICAL SCHEDULES

ISSUE DATES

11-16-2017 ADDENDUM NO. 2  
10-25-2017 BIDS  
09-27-2017 OWNER REVIEW

DATE ISSUED FOR:

DRAWN JTH

CHECKED DAC

APPROVED DAC

PROJECT NO.

17071

DRAWING NO.

M7.2

### FAN SCHEDULE

| UNIT IDENTIFICATION | SYSTEM SERVED | TYPE        | AIRFLOW CFM | T.S.P. IN. W.G. | MINIMUM WHEEL DIAMETER INCHES | RPM  | CLASS | ARRANGEMENT | OUTLET VELOCITY FPM | MOTOR |    |      |            | MODULATION/CONTROL TYPE | ELECTRICAL |       | MAXIMUM SOUND POWER LEVELS |                                  |             |             |             |              |              |                              |              |            |             |             | MODEL NUMBER | REMARKS |             |              |              |              |              |
|---------------------|---------------|-------------|-------------|-----------------|-------------------------------|------|-------|-------------|---------------------|-------|----|------|------------|-------------------------|------------|-------|----------------------------|----------------------------------|-------------|-------------|-------------|--------------|--------------|------------------------------|--------------|------------|-------------|-------------|--------------|---------|-------------|--------------|--------------|--------------|--------------|
|                     |               |             |             |                 |                               |      |       |             |                     | BHP   | HP | RPM  | DRIVE TYPE |                         | VOLTS      | PHASE | OPTIONS/ACCESSORIES        | UNIT DISCHARGE Lw BY OCTAVE BAND |             |             |             |              |              | UNIT INLET Lw BY OCTAVE BAND |              |            |             |             |              |         |             |              |              |              |              |
|                     |               |             |             |                 |                               |      |       |             |                     |       |    |      |            |                         |            |       |                            | 63 HZ (DB)                       | 125 HZ (DB) | 250 HZ (DB) | 500 HZ (DB) | 1000 HZ (DB) | 2000 HZ (DB) | 4000 HZ (DB)                 | 8000 HZ (DB) | 63 HZ (DB) | 125 HZ (DB) | 250 HZ (DB) |              |         | 500 HZ (DB) | 1000 HZ (DB) | 2000 HZ (DB) | 4000 HZ (DB) | 8000 HZ (DB) |
| VF-1                | SUPPLY        | CENTRIFUGAL | 11,000      | 0.4             | 30.5                          | 777  | ---   | INLINE      | 909                 | 3.94  | 5  | 1725 | BELT       | VFC                     | 460        | 3     | ---                        | 89                               | 93          | 82          | 72          | 69           | 59           | 51                           | 49           | 86         | 92          | 86          | 78           | 77      | 74          | 69           | 65           | BSQ-300-50   | NOTE 3       |
| VF-2                | EXHAUST       | CENTRIFUGAL | 4,000       | 0.4             | 16.625                        | 1420 | ---   | INLINE      | 1142                | 0.92  | 1  | 1725 | BELT       | VFC                     | 460        | 3     | ---                        | 84                               | 84          | 82          | 75          | 64           | 57           | 52                           | 48           | 81         | 83          | 86          | 81           | 72      | 72          | 70           | 64           | BSQ-160-10   |              |

NOTE:  
 1. REFER TO SCHEDULES GENERAL NOTES.  
 2. MODEL NUMBERS ARE GREENHECK UNLESS OTHERWISE NOTED.  
 3. PROVIDE MANUFACTURED FILTER BOX ASSEMBLY WITH FAN.

### POWER VENTILATOR SCHEDULE

| UNIT IDENTIFICATION | SYSTEM SERVED | TYPE        | AIRFLOW CFM | T.S.P. IN. W.G. | TIP SPEED FPM | FAN RPM | MOTOR |      |      |            | CURB HEIGHT INCHES | MODULATION/CONTROL TYPE | ELECTRICAL |       | UNIT INLET Lw BY OCTAVE BAND |            |             |             |             |              |              |              |              |      |         |             | MODEL NUMBER | REMARKS    |        |     |           |           |        |
|---------------------|---------------|-------------|-------------|-----------------|---------------|---------|-------|------|------|------------|--------------------|-------------------------|------------|-------|------------------------------|------------|-------------|-------------|-------------|--------------|--------------|--------------|--------------|------|---------|-------------|--------------|------------|--------|-----|-----------|-----------|--------|
|                     |               |             |             |                 |               |         | BHP   | HP   | RPM  | DRIVE TYPE |                    |                         | VOLTS      | PHASE | OPTIONS/ACCESSORIES          | 63 HZ (DB) | 125 HZ (DB) | 250 HZ (DB) | 500 HZ (DB) | 1000 HZ (DB) | 2000 HZ (DB) | 4000 HZ (DB) | 8000 HZ (DB) |      |         |             |              |            |        |     |           |           |        |
|                     |               |             |             |                 |               |         |       |      |      |            |                    |                         |            |       |                              |            |             |             |             |              |              |              |              | EF-1 | EXHAUST | CENTRIFUGAL |              |            | 6,700  | 0.4 | 7263      | 1156      | 2.36   |
| EF-2                | FILTRATION    | CENTRIFUGAL | 1,600       | 0.2             | 2988          | 67      | 0.12  | 1/2  | 1000 | DIRECT     | 18                 | ECM                     | 120        | 1     | A                            | 68         | 73          | 67          | 62          | 62           | 58           | 52           | 47           | 47   | 45      | 36          | 31           | CUE-161-VG | NOTE 3 |     |           |           |        |
| EF-3                | CHLORINE      | CENTRIFUGAL | 235         | .15             | 2746          | 1291    | 0.01  | 1/10 | 1725 | DIRECT     | 18                 | ECM                     | 120        | 1     | A                            | 65         | 63          | 58          | 47          | 41           | 40           | 33           | 29           |      |         |             |              |            |        |     | CUE-70-VG | NOTE 3    |        |
| EF-4                | ACID          | CENTRIFUGAL | 165         | .15             | 2853          | 1341    | 0.02  | 1/10 | 1725 | DIRECT     | 18                 | ECM                     | 120        | 1     | A                            | 61         | 61          | 58          | 50          | 47           | 45           | 36           | 31           |      |         |             |              |            |        |     |           | CUE-65-VG | NOTE 3 |

NOTE:  
 1. REFER TO SCHEDULES GENERAL NOTES.  
 2. MODEL NUMBERS ARE GREENHECK UNLESS OTHERWISE NOTED.  
 3. PROVIDE HI-PRO POLYESTER COATING.

### SPLIT SYSTEM AIR CONDITIONING UNIT SCHEDULE

| INDOOR UNIT         |                    |                |                  |            |              |           |                           |        |              |            |       |     |     | OUTDOOR UNIT |                     |                       |                          |                        |             |           |                         |            |       |     |     |              |             | MODEL NUMBER | REMARKS |
|---------------------|--------------------|----------------|------------------|------------|--------------|-----------|---------------------------|--------|--------------|------------|-------|-----|-----|--------------|---------------------|-----------------------|--------------------------|------------------------|-------------|-----------|-------------------------|------------|-------|-----|-----|--------------|-------------|--------------|---------|
| UNIT IDENTIFICATION | TOTAL CAPACITY MBH | EVAPORATOR FAN |                  |            | COOLING COIL |           |                           | FILTER |              | ELECTRICAL |       |     |     | MODEL NUMBER | UNIT IDENTIFICATION | CONDENSING SECTION    |                          |                        |             |           | MODULATION/CONTROL TYPE | ELECTRICAL |       |     |     | MODEL NUMBER |             |              |         |
|                     |                    | AIRFLOW CFM    | NUMBER FANS EACH | WATTS EACH | E.D.B. °F    | E.W.B. °F | MINIMUM FACE AREA SQ. FT. | EFF. % | AREA SQ. FT. | VOLTS      | PHASE | FLA | MOP |              |                     | NUMBER OF COMPRESSORS | NUMBER OF CONTROL STAGES | AMBIENT TEMPERATURE °F | AIRFLOW CFM | FAN WATTS |                         | VOLTS      | PHASE | FLA | MOP |              |             |              |         |
| ACU-1               | 22.0               | 530            | 1                | 43         | 72           | 60        | ---                       | 25-30  | ---          | 208        | 1     | -   | -   | FTXS24DVJYU  | ACCU-601            | 1                     | MODULATING               | 95                     | 1752        | 53        | AUTO                    | 208        | 1     | 5.3 | 20  | RX24FVJU     | NOTES 3 & 4 |              |         |
| ACU-2               | 22.0               | 530            | 1                | 43         | 72           | 60        | ---                       | 25-30  | ---          | 208        | 1     | -   | -   | FTXS24DVJYU  | ACCU-602            | 1                     | MODULATING               | 95                     | 1752        | 53        | AUTO                    | 208        | 1     | 5.3 | 20  | RX24FVJU     | NOTES 3 & 4 |              |         |

NOTE:  
 1. REFER TO SCHEDULES GENERAL NOTES.  
 2. MODEL NUMBERS DARK UNLESS OTHERWISE NOTED.  
 3. UNITS SHALL BE CAPABLE OF OPERATING DOWN TO 0 DEG. F.  
 4. INDOOR UNIT POWER FEED THROUGH OUTDOOR UNIT.

### PUMP SCHEDULE

| UNIT IDENTIFICATION | SYSTEM SERVED | LOCATION    | TYPE   | COUPLING TYPE | WATERFLOW GPM | FLUID TYPE | COLDEST SYSTEM OPERATING TEMP. °F FOR PUMP SELECTION | PUMP HEAD FT. | OVERLOAD GPM    | MINIMUM EFFICIENCY % | MOTOR |     |      | MODULATION/CONTROL TYPE | ELECTRICAL |       | MODEL NUMBER | REMARKS |                     |
|---------------------|---------------|-------------|--------|---------------|---------------|------------|--|---------------|-----------------|----------------------|-------|-----|------|-------------------------|------------|-------|--------------|---------|---------------------|
|                     |               |             |        |               |               |            |  |               |                 |                      | BHP   | HP  | RPM  |                         | VOLTS      | PHASE |              |         | OPTIONS/ACCESSORIES |
| CP-1                | DHW RETURN    | STORAGE-106 | INLINE | CLOSE         | 1.2           | WATER      | 40   | 7             | NON-OVERLOADING | ---                  | ---   | 1/6 | 3300 | AUTO                    | 120        | 1     | ---          | PL-35   |                     |

NOTE:  
 1. REFER TO SCHEDULES GENERAL NOTES.  
 2. MODEL NUMBER ARE BELL & GOSSETT UNLESS OTHERWISE NOTED.  
 3. FLUID TYPE: W = WATER.

### FUEL FIRED DOMESTIC WATER HEATER SCHEDULE

| UNIT IDENTIFICATION | STORAGE CAPACITY GALLONS | FUEL TYPE   | FIRING RATE MBH | RECOVERY GPH | E.W.T. °F | L.W.T. °F | MODULATION/CONTROL TYPE | ELECTRICAL |       |     |     |                     | MODEL NUMBER | REMARKS |
|---------------------|--------------------------|-------------|-----------------|--------------|-----------|-----------|-------------------------|------------|-------|-----|-----|---------------------|--------------|---------|
|                     |                          |             |                 |              |           |           |                         | VOLTS      | PHASE | FLA | MOP | OPTIONS/ACCESSORIES |              |         |
| DWH-1               | 320                      | NATURAL GAS | 285             | 332          | 40        | 140       | AUTO                    | 120        | 1     | 6.7 | 15  | B                   | AWN286PM     | NOTE 3  |

NOTE:  
 1. REFER TO SCHEDULES GENERAL NOTES.  
 2. MODEL NUMBERS ARE LOCHINVAR UNLESS OTHERWISE NOTED.  
 3. PROVIDE LOCHINVAR RGA0318 STORAGE TANK.

### THERMOSTATIC MIXING VALVE SCHEDULE

| UNIT IDENTIFICATION | MINIMUM FLOW GPM | MAXIMUM FLOW GPM | PRESSURE DROP AT MAXIMUM FLOW PSIG | MODEL NUMBER | REMARKS |
|---------------------|------------------|------------------|------------------------------------|--------------|---------|
| MV-1                | 2                | 85               | 4                                  | S59-3080     |         |

NOTE:  
 1. MODEL NUMBERS ARE BRADLEY UNLESS OTHERWISE NOTED.

### EXPANSION TANK SCHEDULE

| UNIT IDENTIFICATION | SYSTEM SERVED  | ESTIMATED TOTAL SYSTEM VOLUME GALLON | TYPE      | OPERATING PRESSURE |              | OPERATING TEMPERATURE |            | TANK VOLUME GALLON | ACCEPTANCE VOLUME GALLON | DIMENSIONS      |               | MODEL NUMBER | REMARKS |
|---------------------|----------------|--------------------------------------|-----------|--------------------|--------------|-----------------------|------------|--------------------|--------------------------|-----------------|---------------|--------------|---------|
|                     |                |                                      |           | MINIMUM PSIG       | MAXIMUM PSIG | MINIMUM °F            | MAXIMUM °F |                    |                          | DIAMETER INCHES | HEIGHT INCHES |              |         |
| ET-1                | DOMESTIC WATER | 345                                  | DIAPHRAGM | ---                | 150          | 40                    | 130        | 6.4                | 3                        | 12              | 15-5/8        | PTA-12       |         |

NOTE:  
 1. MODEL NUMBERS ARE BELL & GOSSETT UNLESS OTHERWISE NOTED.

### GRILLE, REGISTER, AND DIFFUSER SCHEDULE

| UNIT IDENTIFICATION | TYPE     | FACE SIZE  | NECK SIZE | FRAME TYPE | ACCESSORY            | CONSTRUCTION | FINISH | MODEL NUMBER | REMARKS |
|---------------------|----------|------------|-----------|------------|----------------------|--------------|--------|--------------|---------|
| S-1                 | GRILLE   | NK + 1-3/4 | SEE PLANS | NOTE 2     | ---                  | ALUMINUM     | WHITE  | S300FL       |         |
| E-1                 | REGISTER | 24x12      | SEE PLANS | NOTE 2     | OPPOSED BLADE DAMPER | ALUMINUM     | WHITE  | PAR-AA       |         |
| E-2                 | GRILLE   | NK + 1-3/4 | SEE PLANS | NOTE 2     | ---                  | ALUMINUM     | WHITE  | 33RL         |         |
| T-1                 | GRILLE   | NK + 1-3/4 | SEE PLANS | NOTE 2     | ---                  | ALUMINUM     | WHITE  | 33RL         |         |

NOTE:  
 1. MODEL NUMBERS ARE TITUS UNLESS OTHERWISE NOTED.  
 2. COORDINATE FRAME TYPE WITH ARCHITECTURAL TRADES, PROVIDE PLASTER FRAME TRAP WHERE REQUIRED.

### PLUMBING CONNECTION SCHEDULE

| UNIT IDENTIFICATION | CW INCHES | HW INCHES | SAN INCHES | VENT INCHES | REMARKS              |
|---------------------|-----------|-----------|------------|-------------|----------------------|
|                     |           |           |            |             |                      |
| UR-1                | 3/4       | -         | 2          | 1 1/2       |                      |
| WC-1                | 1 1/2     | -         | 4          | 2           |                      |
| LAV-1               | 1/2       | 1/2       | 1 1/2      | 1 1/2       |                      |
| SK-1                | 3/4       | 3/4       | 1 1/2      | 1 1/2       |                      |
| SS-1                | 3/4       | 3/4       | 3          | -           |                      |
| SH-1                | 3/4       | 3/4       | -          | -           | PROVIDE MIXING VALVE |
| SH-2                | 3/4       | 3/4       | -          | -           | PROVIDE MIXING VALVE |
| FD-1                | -         | -         | 3          | -           |                      |
| FD-2                | -         | -         | 4          | -           |                      |

NOTE: INDIVIDUAL WATER LINE BRANCHES, WASTE LINES, VENTS, AND TRAPS FOR CONNECTION TO INDIVIDUAL FIXTURES, FIXTURE FITTINGS, AND SPECIALTIES SHALL BE IN ACCORDANCE WITH THE FOLLOWING SCHEDULE OR AS INDICATED ON DRAWINGS, WHICHEVER IS GREATER.

### SCHEDULES GENERAL NOTES:

TYPICAL FOR ALL SCHEDULE SHEETS:

- REFER TO ELECTRICAL STANDARD SCHEDULES, ONE LINE DIAGRAM AND PANEL SCHEDULES FOR ADDITIONAL ELECTRICAL INFORMATION.
- PROVIDE THE FOLLOWING FACTORY-WIRED ELECTRICAL OPTIONS/ACCESSORIES WHERE INDICATED IN SCHEDULE:
  - A - NON-FUSED DISCONNECT SWITCH
  - B - UNIT SHALL BE SINGLE POINT ELECTRICAL CONNECTION WITH FACTORY INSTALLED DISCONNECTING MEANS AND ALL REQUIRED STARTERS AND CONTROLS
  - C - SERVICE RECEPTACLE
  - D - FUSED DISCONNECT SWITCH
  - E - COMBINATION STARTER
  - F - UNIT SHALL HAVE (2) SINGLE POINT CONNECTIONS WITH FACTORY INSTALLED DISCONNECTING MEANS AND ALL REQUIRED STARTERS AND CONTROLS. (1) CONNECTION SHALL BE FOR CONDENSING SECTION AND (1) CONNECTION SHALL BE FOR THE REMAINDER OF THE UNIT.
- FOR MODULATION/CONTROL TYPE COLUMN, "VFC" INDICATES VARIABLE FREQUENCY CONTROLLERS, "AUTO" INDICATES AUTOMATIC OPERATION (CONTROLLED BY TEMPERATURE CONTROLS OR SELF CONTAINED CONTROLS), "MANUAL" INDICATES HAND OPERATION.
- IF VARIABLE FREQUENCY CONTROLLERS ARE INDICATED TO BE PROVIDED AND ARE NOT INSTALLED INTEGRAL TO THE UNIT, VARIABLE FREQUENCY CONTROLLERS SHALL BE SUPPLIED BY THE MECHANICAL CONTRACTOR (UNLESS OTHERWISE NOTED) AND INSTALLED BY THE ELECTRICAL CONTRACTOR INCLUDING THE LINE SIDE AND LOAD SIDE WIRING TO THE MOTOR AND INCLUDING MISCELLANEOUS STEEL REQUIRED FOR THE SUPPORT AND MOUNTING OF THE VFC. REFER TO FLOOR PLANS FOR LOCATION.
- WHERE EQUIPMENT IS INDICATED TO HAVE A SINGLE POINT ELECTRICAL CONNECTION, THAT EQUIPMENT SHALL COME COMPLETE WITH FACTORY INSTALLED STARTERS, MOTOR OVERLOAD PROTECTION, CONTACTORS, FUSING AND ALL NECESSARY INTERNAL WIRING AND CONTROLS. PROVIDE A FACTORY MOUNTED UNIT DISCONNECTING MEANS WHERE THE ELECTRICAL CONTRACTOR SHALL MAKE SINGLE POINT CONNECTION. INSTALL PACKAGED EQUIPMENT SUCH THAT THE ELECTRICAL CONNECTION AND CONTROLS ARE ACCESSIBLE AND HAVE CLEARANCES MEETING THE NATIONAL ELECTRICAL CODE.
- WHERE PACKAGED EQUIPMENT IS PROVIDED, NAMEPLATE MUST INDICATE MAXIMUM OVERCURRENT PROTECTION BY HAZOP RATED CIRCUIT BREAKERS OR FUSES. IF FUSE PROTECTION ONLY IS INDICATED, PROVIDE A FUSIBLE DISCONNECT AND FUSES WITH THE UNIT.
- WHERE EQUIPMENT IS DESIGNATED BY MANUFACTURER AND MODEL NUMBER, THIS IS THE BASIS OF DESIGN. IF THE CONTRACTOR ELECTS TO PROVIDE EQUIPMENT BY OTHER SPECIFIED MANUFACTURERS OR PROPOSED ALTERNATE EQUIPMENT BY THE BASIS OF DESIGN MANUFACTURER, THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY REVISIONS TO ELECTRICAL REQUIREMENTS, STRUCTURAL LOADING, OR ARCHITECTURAL APPURTENANCES AND SHALL INCLUDE THE COST OF SUCH REVISIONS IN HIS BID.
- WHERE EQUIPMENT IS SCHEDULED TO INCLUDE A SERVICE RECEPTACLE, PROVIDE A FACTORY MOUNTED SERVICE RECEPTACLE WITH APPROPRIATE FUSES AND TRANSFORMERS CONNECTED ON THE LINE SIDE OF THE UNIT DISCONNECT. PROVIDE A NAMEPLATE ON THE DISCONNECT SWITCH INDICATING THE PRESENCE OF LIVE POWER TO THE SERVICE RECEPTACLE WHEN THE UNIT DISCONNECT IS IN THE OFF POSITION.
- SIZE ALL EQUIPMENT FEEDERS BASED ON THE LISTED MOP (MAXIMUM OVERCURRENT PROTECTION). REFER TO THE FEEDER AND BRANCH CIRCUIT SIZING SCHEDULE ON THE ELECTRICAL STANDARD SCHEDULES SHEET.

### SEWAGE PUMP AND SUMP PUMP SCHEDULE

| UNIT IDENTIFICATION | SYSTEM SERVED | SIMPLEX OR DUPLEX | PUMP     |               |                 |         | BASIN |              |                 |              | MODULATION/CONTROL TYPE | ELECTRICAL |       |       | MODEL NUMBER | REMARKS |                     |
|---------------------|---------------|-------------------|----------|---------------|-----------------|---------|-------|--------------|-----------------|--------------|-------------------------|------------|-------|-------|--------------|---------|---------------------|
|                     |               |                   | QUANTITY | FLOW EACH GPM | W.P.D. FT. HEAD | HP EACH | RPM   | CONSTRUCTION | DIAMETER INCHES | DEPTH INCHES |                         | COVER TYPE | VOLTS | PHASE |              |         | OPTIONS/ACCESSORIES |
| SP-1                | DRAIN TILE    | SIMPLEX           | 1        | 30            | 28              | 1       | 1750  | FIBERGLASS   | 24              | 105          | cov type                | AUTO       | 208   | 3     | B            | 1601    |                     |


NOTE:  
 1. REFER TO SCHEDULES GENERAL NOTES.  
 2. MODEL NUMBERS ARE WEL UNLESS OTHERWISE NOTED.

C:\2017\2017-0248-00\CAD\2017-0248-M7-SH.dwg, M7.2, 11/15/2017 5:25:39 PM, Eric C. Deska, \_Default.pc3, 0.16482, Peter Basso Associates Inc.





THE FOLLOWING DIMENSION EQUALS ONE INCH WHEN PRINTED TO SCALE.



**POWER AND AUXILIARY SYSTEMS PLAN**  
SCALE: 1/8" = 1'-0"

**ELECTRICAL GENERAL NOTES:**

1. THESE DRAWINGS REPRESENT THE GENERAL EXTENT AND ARRANGEMENT OF SYSTEMS, BUT ARE NOT TO BE CONSIDERED FABRICATION DRAWINGS. COORDINATE WITH OTHER TRADES, AND PROVIDE EACH SYSTEM COMPLETE, INCLUDING ALL NECESSARY COMPONENTS, FITTINGS, AND OFFSETS.
2. INSTALL SYSTEMS SUCH THAT REQUIRED CLEARANCE AND SERVICE ACCESS SPACE IS PROVIDED AROUND ALL MECHANICAL AND ELECTRICAL EQUIPMENT, AND AROUND ANY COMPONENTS WHICH REQUIRE SERVICE ACCESS.
3. COORDINATE AND PROVIDE ACCESS DOORS WITHIN INACCESSIBLE CEILING, SHAFT, AND CHASE AREAS FOR ALL COMPONENTS WHICH REQUIRE SERVICE ACCESS. REFER TO ARCHITECTURAL DRAWINGS FOR CEILING TYPES.
4. PROVIDE SUPPLEMENTARY STEEL AS REQUIRED FOR THE PROPER SUPPORT OF ALL SYSTEMS.
5. TRANSFORMER SECONDARY CONDUCTORS SHALL BE SIZED IN ACCORDANCE WITH TRANSFORMER CIRCUIT SIZING SCHEDULE SHOWN ON "ELECTRICAL STANDARD SCHEDULES DRAWING" UNLESS OTHERWISE NOTED.
6. MOTOR CIRCUIT PROTECTION SHALL BE SIZED IN ACCORDANCE WITH MOTOR CIRCUIT SIZING SCHEDULES SHOWN ON "ELECTRICAL STANDARD SCHEDULES DRAWING" UNLESS OTHERWISE NOTED.
7. COORDINATE THE MOUNTING HEIGHTS OF DEVICES WITH ARCHITECTURAL ELEVATIONS AND THE TRADES INSTALLING THE WORK.
8. REFER TO MECHANICAL SCHEDULE SHEETS FOR ELECTRICAL REQUIREMENTS FOR MECHANICAL EQUIPMENT. PROVIDE ALL CONNECTIONS, STARTERS, DISCONNECTS, ETC. AS REQUIRED BY SCHEDULES AND WHERE NOTED ELSEWHERE. VERIFY REQUIREMENTS OF ALL MECHANICAL EQUIPMENT WITH SHOP DRAWINGS SUBMITTALS. NOTIFY ENGINEER OF ANY CONFLICTS BETWEEN EQUIPMENT SUBMITTALS AND ELECTRICAL DRAWINGS. WHERE CIRCUIT SIZES ARE SHOWN ON THE ELECTRICAL DRAWINGS THAT DIFFER FROM WHAT IS INDICATED ON THE MECHANICAL SCHEDULES, PROVIDE THE CIRCUIT OF HIGHER AMPACITY.
9. REFER TO TEMPERATURE CONTROLS SHEETS FOR REQUIRED MOTOR CONTROLLERS. PROVIDE ALL ACCESSORIES INDICATED.
10. PROVIDE THE DESIGN AND INSTALLATION FOR A COMPLETE AND FUNCTIONAL FIRE ALARM SYSTEM IN ACCORDANCE WITH SPECIFICATIONS, DRAWINGS, AND ALL APPLICABLE CODES. THE FIRE ALARM VENDOR SHALL PROVIDE LAYOUT DRAWINGS INDICATING THE REQUIRED QUANTITIES AND LOCATIONS OF MANUAL PULL STATIONS, NOTIFICATION APPLIANCES, SMOKE AND HEAT DETECTORS, CONTROL MODULES, INTERFACE MODULES, MODULES FOR SPRINKLER FLOW AND TAMPER SWITCHES, ALL CONTROL PANELS, POWER SUPPLIES, ADDITIONAL DEVICES AND EQUIPMENT REQUIRED. COORDINATE LOCATIONS OF DEVICES WITH ARCHITECTURAL FINISHES AND REFLECTED CEILING PLANS, INCLUDING ADDITIONAL SMOKE AND HEAT DETECTORS REQUIRED FOR NON-SMOOTH CEILING APPLICATIONS. INCLUDE ALLOWANCES FOR ADJUSTMENT OF DEVICES BY THE ARCHITECT AT THE TIME OF SUBMITTAL TO COORDINATE WITH BUILDING FINISHES AND OTHER CEILING ELEMENTS.

**CONSTRUCTION KEY NOTES:**

1. PROVIDE 6 POSITION ON/OFF SELECTOR SWITCH STATION FOR POOL PUMPS PPI, PP2, PP3, PP4, POOL DECK LIGHTING AND IN-WATER LIGHTING.



REGISTRATION SEAL

CONSULTANT

PROJECT TITLE  
**Ford Woods Park Pool**

City of Dearborn

DRAWING TITLE  
**POWER AND AUXILIARY SYSTEMS PLAN**

ISSUE DATES


|            |                |
|------------|----------------|
| 11-16-2017 | ADDENDUM NO. 2 |
| 10-25-2017 | BIDS           |
| 09-27-2017 | OWNER REVIEW   |

|               |             |
|---------------|-------------|
| DATE:         | ISSUED FOR: |
| DRAWN: ECD    |             |
| CHECKED: ECD  |             |
| APPROVED: SAG |             |

PROJECT NO.  
**17071**


DRAWING NO.  
**E3.1**

g:\2017\2017-0248-00\CAD\2017-0248-E3-P1.dwg, E3.1, 11/15/2017 4:56:50 PM, Eric C. Deska, \_Detail.pcs3\_0.16482, Peter Basso Associates Inc.




LOAD:


|       |        |
|-------|--------|
| RP-FW | 126A   |
| PP1   | 27A    |
| PP2   | 11A    |
| PP3   | 21A    |
| PP4   | 7.6A   |
| EF-1  | 4.8A   |
| VF-1  | 7.5A   |
| VF-2  | 2.1A   |
| TOTAL | 202.5A |




**GRADE RECEPTACLE DETAIL**  
NO SCALE



**BOLLARD BASE DETAIL**  
NO SCALE



**DRY TYPE DISTRIBUTION TRANSFORMER GROUNDING ARRANGEMENT**  
NO SCALE



**POOL ENVIRONMENT SCHEMATIC BONDING DETAIL**  
NO SCALE

| PANELBOARD RP-FW |           |                                     |         |    |      |      |      |      |      |    |                                    |           |    |
|------------------|-----------|-------------------------------------|---------|----|------|------|------|------|------|----|------------------------------------|-----------|----|
| #                | LOAD TYPE | DESCRIPTION                         | CB TYPE | CB | VA   | RA   | RM   | RC   | VA   | CB | DESCRIPTION                        | LOAD TYPE | #  |
| 1                | L         | LIGHTING - LOBBY                    |         | 20 | 1250 | 2100 |      |      | 900  | 20 | RECEPT - OFFICE LOBBY              | R         | 2  |
| 2                | L         | LIGHTING - LOBBY                    |         | 20 | 1900 |      | 2300 |      | 700  | 20 | RECEPT - RECEPTION                 | R         | 4  |
| 3                | L         | LIGHTING - TOILET, LOCKER, CORRIDOR |         | 20 | 1110 |      | 2370 | 1500 | 25   |    | RECEPT - LOBBY, TOILET             | R         | 8  |
| 4                | L         | LIGHTING - OFFICE, SHOWER           |         | 20 | 1090 | 2090 |      |      | 1000 | 20 | RECEPT - WENDING                   | R         | 8  |
| 5                | L         | LIGHTING - WALKER, BENCHES          |         | 20 | 1580 |      | 2080 |      | 1000 | 20 | RECEPT - WENDING                   | R         | 10 |
| 6                | L         | LIGHTING - J.C. STORAGE, FILTRATION |         | 20 | 315  |      | 1310 | 1000 | 20   |    | RECEPT - WENDING                   | R         | 13 |
| 7                | L         | LIGHTING - EXTERIOR                 |         | 20 | 160  | 1240 |      | 2500 | 1080 | 20 | RECEPT - WALKWAY, FIRST AID        | R         | 14 |
| 8                | L         | SPARE                               |         | 20 | 2000 |      |      |      | 20   |    | RECEPT - FIRST AID, RETROREFLECTOR | R         | 18 |
| 9                | M         |                                     |         | 20 | 500  |      | 500  |      | 20   |    | RECEPT - FIRST AID, ICE            | R         | 18 |
| 10               | M         |                                     |         | 20 | 500  | 500  |      |      | 20   |    | RECEPT - FIRST AID                 | R         | 20 |
| 11               | NC        | DOMESTIC WATER HEATER (DWH-1)       |         | 20 | 500  |      | 500  |      | 20   |    | RECEPT - FIRST AID, MICROWAVE      | R         | 22 |
| 12               | NC        | AC-1/200-1                          |         | 20 | 550  |      | 550  | 1450 | 900  | 20 | RECEPT - EXTERIOR                  | R         | 24 |
| 13               | NC        | AC-1/200-1                          |         | 20 | 550  |      | 550  |      | 20   |    | RECEPT - J.C. STORAGE, FILTRATION  | R         | 26 |
| 14               | NC        | AC-1/200-1                          |         | 20 | 550  |      | 550  |      | 20   |    | RECEPT - J.C. STORAGE, FILTRATION  | R         | 28 |
| 15               | NC        | AC-1/200-1                          |         | 20 | 550  |      | 550  |      | 20   |    | RECEPT - J.C. STORAGE, FILTRATION  | R         | 30 |
| 16               | M         | SP-1                                |         | 20 | 1176 | 1176 |      |      | 20   |    | WATER LEVEL CONTROLLER             | R         | 32 |
| 17               | M         | SP-2                                |         | 20 | 250  |      | 250  |      | 20   |    | WATER LEVEL CONTROLLER             | R         | 34 |
| 18               | M         | SP-3                                |         | 20 | 250  |      | 250  |      | 20   |    | WATER LEVEL CONTROLLER             | R         | 36 |
| 19               | M         | SP-4                                |         | 20 | 250  |      | 250  |      | 20   |    | WATER LEVEL CONTROLLER             | R         | 38 |
| 20               | NC        | CONTROL PANEL                       |         | 20 | 700  |      | 700  |      | 20   |    | CONTROL PANEL                      | R         | 40 |
| 21               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 42 |
| 22               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 44 |
| 23               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 46 |
| 24               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 48 |
| 25               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 50 |
| 26               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 52 |
| 27               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 54 |
| 28               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 56 |
| 29               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 58 |
| 30               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 60 |
| 31               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 62 |
| 32               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 64 |
| 33               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 66 |
| 34               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 68 |
| 35               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 70 |
| 36               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 72 |
| 37               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 74 |
| 38               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 76 |
| 39               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 78 |
| 40               | SPARE     |                                     |         | 20 |      |      |      |      | 20   |    |                                    |           | 80 |

| BRANCH CIRCUIT CONNECTED LOAD: | FEEDER DEMAND LOAD: | DISBURSEMENT LOAD: | NOTES: |
|--------------------------------|---------------------|--------------------|--------|
| CONTINUOUS LOAD (C)            | X 125%              | X 100%             |        |
| NON-CONTINUOUS LOAD (NC)       | X 100%              | X 100%             |        |
| KITCHEN LOAD (K)               | X 100%              | X 100%             |        |
| RECEPTACLE BASE LOAD (R)       | X 100%              | X 100%             |        |
| RECEPTACLE DEMAND LOAD (RD)    | X 100%              | X 100%             |        |
| LIGHTING LOAD (L)              | X 100%              | X 100%             |        |
| TRACK LIGHTING (T)             | (30VA/2FT)          | X 125%             |        |
| MOTOR, HIGHEST LOAD (M)        | X 125%              | X 100%             |        |
| MOTOR, REMAINING LOAD (MR)     | X 100%              | X 100%             |        |
| TOTAL LOAD                     | 50.8A               | 50.8A              |        |
| TOTAL AMP                      | 181.1A              | 181.1A             |        |

Copyright 2014 by Peter Basso Associates, Inc.

**GENERAL NOTES:**

- THESE DRAWINGS REPRESENT THE GENERAL EXTENT AND ARRANGEMENT OF SYSTEMS, BUT ARE NOT TO BE CONSIDERED FABRICATION DRAWINGS. COORDINATE WITH OTHER TRADES, AND PROVIDE EACH SYSTEM COMPLETE, INCLUDING ALL NECESSARY COMPONENTS, FITTINGS, AND OFFSETS.
- FEEDER AND BRANCH CIRCUIT CONDUCTORS SHALL BE SIZED IN ACCORDANCE WITH THE "FEEDER AND BRANCH CIRCUIT SIZING SCHEDULE-GENERAL PURPOSE" ON THE "ELECTRICAL STANDARD SCHEDULES DRAWING" UNLESS SPECIFICALLY NOTED OTHERWISE.
- TRANSFORMER SECONDARY CONDUCTORS SHALL BE SIZED IN ACCORDANCE WITH THE "TRANSFORMER CIRCUIT SIZING SCHEDULE-GENERAL PURPOSE" ON THE "ELECTRICAL STANDARD SCHEDULES DRAWING" UNLESS SPECIFICALLY NOTED OTHERWISE.
- MOTOR CIRCUIT PROTECTION SHALL BE SIZED IN ACCORDANCE WITH THE MOTOR CIRCUIT SIZING SCHEDULES ON THE "ELECTRICAL STANDARD SCHEDULES DRAWING" UNLESS SPECIFICALLY NOTED OTHERWISE.
- BRANCH CIRCUIT CONDUCTORS, FEEDERS, AND BRANCH CIRCUIT OVERCURRENT PROTECTION ARE SIZED AT 125% OF THE TOTAL CONTINUOUS AND NON CONTINUOUS LOAD FOR LIGHTING AND MOTOR LOADS THAT RUN CONTINUOUSLY FOR THREE HOURS OR MORE (NEC 210.19 A, 210.20 A, AND 215.2 A). DEMAND AND CONNECTED LOADS ARE CALCULATED PER NEC 220.
- VARIABLE FREQUENCY CONTROLLERS (VFC) FURNISHED BY MECHANICAL TRADES. ELECTRICAL CONTRACTOR SHALL INSTALL VFC, PROVIDE POWER FEEDER FROM DISTRIBUTION EQUIPMENT TO VFC AND PROVIDE POWER FEEDER FROM VFC TO MOTOR. REFER TO SPECIFICATIONS FOR APPLICATION OF VFC POWER CABLE FROM VFC TO MOTOR.



REGISTRATION SEAL

CONSULTANT

PROJECT TITLE  
**Ford Woods Park Pool**

City of Dearborn

DRAWING TITLE  
**ONE LINE DIAGRAM AND PANEL SCHEDULES**

ISSUE DATES

11-16-2017 ADDENDUM NO. 2  
10-25-2017 BIDS  
09-27-2017 OWNER REVIEW

DATE: ISSUED FOR:

DRAWN: ECD  
CHECKED: ECD  
APPROVED: SAG

PROJECT NO.  
**17071**

DRAWING NO.

**E5.1**

# City of Dearborn Recreation & Parks Department

## Sign-In Sheet

Meeting Date and Time: Monday, November 13, 2017

Purpose: Final work Pool Replacement Project

| NAME<br>(Please print clearly.) | AFFILIATION<br>(If City employee,<br>please list Department.) | EMAIL ADDRESS<br>(Please print clearly.) | TELEPHONE         |
|---------------------------------|---|--|-------------------|
| ERIC PETERSON                   | CITY OF DEARBORN  | epeterson@ci.<br>dearborn.mi.us          | 313-943-2411      |
| DOB FARLEY                      | TMP ARCHITECTURE  | DFARLEY@TMP-ARCHITECTURE                 | .COM 248-338-4961 |
| DANIELLE O'NEAL                 | TMP ARCHITECTURE  | doneal@tmp-architecture.com              | 248-338-4561      |
| Tony Baruzzini                  | Baruzzini Contracting   | tony6baruzzini.com                       | 810 229-8996      |
| DANE FRIDERIKSEN                | B & B POOLS AND SPA   | DANE@BANDBPOOLS.COM                      | 734.427.3247      |
| Danny Chee                      | Brix Corporation  | dchee@brixcorporation.com                | 313-965-0000      |
| Robert Lentz                    | Antler Construction   | lentzdale@yahoo.com                      | 734-404-6459      |
| KENT BROUGHMAN                  | BERNCO INC  | KBROUGHMAN@BERNCO<br>INC.COM             | 586 445 3700      |
| Jacob Alexander                 | Cross Renovation  | jake@stark-EnterprisesLLC.com            | (248) 914-1402    |
| Mike Turri                      | Brenca Contractors  | mturri@brenca.net                        | (586) 758-6000    |
| Greg Orner                      | Rec Dept  | gorner@                                  | 313-943-2804      |

